

COMBINE BUYERS GUIDE

| Model | List price (£) (with recommended table) | Recommended table (m) | Other table sizes available (m) | Grain tank (litres) | Engine make & max harvesting power/max unloading power |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------|---------------------------------|---------------------|--------------------------------------------------------|
| Case-IH | | | | | |
| 140 Series Threshing: one 76cm x 2.79m three-speed variator drive rotor. Separation: as for threshing – 2.80sq m. Sieve area: 5.52sq m. | | | | | |
| 5140 Cross Flow | 249,340 | 5.48 | 4.88-6.70 | 8,810 | FPT 312hp |
| 6140 Cross Flow | 283,733 | 6.70 | 5.48-6.10 | 10,570 | FPT 400hp |
| 7140 Cross Flow | 305,077 | 7.62 | 6.09-9.14 | 10,570 | FPT 449hp |
| 240 Series Threshing: one 76cm x 2.62m three-range hydro-drive rotor. Separation: as for threshing – 2.98sq m. Sieve area: – 6.40sq m. | | | | | |
| 7240 | 347,349 | 9.14 | 7.62-10.7 | 11,100 | FPT 498hp |
| 7240 Accutrac | 405,744 | 9.14 | 7.62-10.8 | 11,100 | FPT 498hp |
| 8240 | 380,280 | 10.7 | 9.14-12.5 | 14,440 | FPT 571hp |
| 8240 Accutrac | 438,387 | 10.7 | 9.14-12.6 | 14,440 | FPT 571hp |
| 9240 | 440,326 | 12.5 | 9.14-10.7 | 14,440 | FPT 634hp |
| 9240 Accutrac | 482,412 | 12.5 | 9.14-10.7 | 14,440 | FPT 634hp |
| Note: "ST" (small tube) rotor standard on all models. Prices include 3050 Series table with 570mm fore-aft knife adjustment. Hydraulic side knives optional. Axial-Flow 140 Series combines have Cross Flow cleaning system for hillside compensation up to 12%; 240 Series have self-levelling shaker shoe assembly for 12% slope compensation. AFS AccuGuide GPS steering – 140 Series £19,110; 240 Series £9495. Traction belt widths 61cm, 72cm and 86cm. 4wd option: 140 Series £16,291; 240 Series £16,292. Distributor: Case IH Agriculture. | | | | | |
| Claas | | | | | |
| Avero 200 Series Threshing: Separation drum + 1.06m x 45cm cylinder + beater. Separation: Four walkers + overhead agitator tine drum – 4.8sq m. Sieve area: 3.0sq m. | | | | | |
| 240 | 124,930 | 4.9 C | 3.7-5.4 | 5,600 | Perkins 205hp |
| Tucano 300 Series Threshing: 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines – 6.78 sq m. Sieve area: 4.25sq m. | | | | | |
| 320 | 157,450 | 6.0 V | 3.7-5.4 | 6,500 | M-B 245hp |
| Tucano 400 Series Threshing: Separation drum + 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines – 7.26sq m. Sieve area: 4.7sq m. | | | | | |
| 420 | 169,210 | 6.0 V | 4.9-6.0 | 7,500 | M-B 245hp |
| 430 | 178,710 | 6.0 V | 4.9-6.0 | 8,000 | M-B 286hp |
| Tucano 400 Series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: Six walkers + overhead agitator tines – 8.75sq m. Sieve area: 5.65sq m. | | | | | |
| 440 | 195,740 | 6.6 V | 6.0-7.7 | 8,500 | M-B 286hp |
| 450 | 211,050 | 7.7 V | 6.0-9.3 | 9,000 | M-B 313hp |
| Tucano 500 Series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: one 57cm x 4.2m vari-speed rotor – n/a sq m. Sieve area: 5.65sq m. | | | | | |
| 570 | 220,800 | 7.7 V | 6.0-9.3 | 9,000 | M-B 354hp |
| Lexion 600 Series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Five walkers + overhead agitator tine drum – 8.23sq m. Sieve area: 4.80sq m. | | | | | |
| 620 | 195,500 | 6.0 V | 5.4-6.6 | 9,000 | M-B 313hp |
| 630 | 202,920 | 6.6 V | 6.0-7.7 | 9,000 | M-B 354hp |
| 630 Montana | 217,910 | 6.6 V | 6.0-7.7 | 9,000 | M-B 354hp |
| Lexion 600 Series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Six walkers + overhead agitator tine drum – 9.85sq m. Sieve area: 5.80sq m. | | | | | |
| 650 | 229,990 | 7.7 V | 6.0-9.3 V | 10,000 | M-B 354hp |
| 660 | 242,780 | 7.7 V | 6.6-9.3 V | 11,000 | M-B 408hp |
| 660 Terra Trac | 276,660 | 7.7 V | 6.6-9.3 V | 11,000 | M-B 435hp |
| 670 | 259,860 | 9.3 V | 6.6-9.3 V | 11,000 | M-B 435hp |
| 670 Montana | 267,890 | 7.7 V | 6.6-9.3 V | 10,000 | M-B 435hp |
| 670 Terra Trac | 298,180 | 9.3 V | 6.6-9.3 V | 11,000 | M-B 435hp |
| Lexion 700 Series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors – 4.32sq m. Sieve area: 5.10sq m. | | | | | |
| 740 | 281,910 | 7.7 V | 6.6-9.3 V | 10,000 | M-B 405hp |
| 750 | 310,480 | 9.3 V | 6.6-9.3 V | 10,000 | M-B 435hp |
| 750 Montana | 323,120 | 9.3 V | 6.6-9.3 V | 10,000 | M-B 435hp |
| 750 Terra Trac | 342,430 | 9.3 V | 6.6-10.8 V | 10,000 | M-B 435hp |
| 760 | 345,070 | 9.3 V | 7.5-10.8 V | 11,000 | Perkins 503hp |
| 760 Terra Trac | 411,370 | 10.5 V | 7.5-10.8 V | 11,000 | Perkins 503hp |
| 760 Montana | 348,320 | 9.3 V | 7.5-9.3 V | 9,000 | Perkins 503hp |
| Lexion 700 Series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors – n/a sq m. Sieve area: 6.20sq m. | | | | | |
| 770 | 389,030 | 10.5 V | 9.3-10.8 V | 12,800 | M-B 585hp |

| | | | | | |
|----------------|---------|--------|-------------|--------|-----------|
| 770 Terra Trac | 434,800 | 12.3 V | 9.3-12.3 V | 12,800 | M-B 585hp |
| 780 Terra Trac | 470,230 | 12.3 V | 10.5-12.3 V | 13,500 | M-B 625hp |

Note: 40kph transmission optional on Lexion 750 Terra Trac and 760 Terra Trac. Montana – automatic chassis levelling 17% lateral, 6% fore-aft. 4-D dynamic sieve 20% slope compensation standard on Lexion 760, 770 and 780, optional on all other models. Laser Pilot laser-scanning auto steer system standard on Lexion 760, 770 and 780, optional on other models. GPS Pilot satellite-guided auto steer optional on all models. Cemos settings advice system and Cemos Automatic optional on all Lexion 700 Series combines. Terra Trac – rubber track suspension undercarriage with 635mm, 735mm or 890mm traction belts. Cutting tables: C – Contour, AC – Auto Contour, V – Auto Contour Vario (with fore-aft knife adjustment). Cruise Pilot automatic forward speed control optional on Lexion 780-650. Optional 4wd available on all models. Distributor: Claas UK.

Deutz-Fahr

6200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 5.28sq m. Sieve area: 4.22sq m.

| | | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----|---------|-------|-----------|
| 6205 Farm-Line | 145,850 | 4.8 | 3.6-5.4 | 7,000 | M-B 250hp |
| 6205 Top-Line | 152,750 | 4.8 | 3.6-5.4 | 7,000 | M-B 250hp |
| 6200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers – 5.28sq m. Sieve area: 4.22sq m. | | | | | |
| 6205 HTS Farm-Line | 153,500 | 4.8 | 3.6-5.4 | 7,000 | M-B 250hp |
| 6205 HTS Top-Line | 160,450 | 4.8 | 3.6-5.4 | 7,000 | M-B 250hp |

7200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 7.36sq m. Sieve area: 5.28sq m.

| | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----|---------|-------|-----------|
| C7205 Farm-Line | 192,050 | 5.4 | 4.2-7.2 | 8,500 | M-B 309hp |
| C7205 Top-Line | 195,700 | 5.4 | 4.2-7.2 | 8,500 | M-B 309hp |
| 7200 Series Threshing: 1.27m x 60cm cylinder+ beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers – 7.36sq m. Sieve area: 5.28sq m. | | | | | |
| C7205 TS Farm-Line | 203,450 | 6.3 | 4.8-7.2 | 8,500 | M-B 309hp |
| C7205 TS Top-Line | 207,850 | 6.3 | 4.8-7.2 | 8,500 | M-B 309hp |
| C7205 TSB Balance | 224,350 | 6.3 | 4.8-7.2 | 8,500 | M-B 309hp |

7200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation: Six walkers – 8.8sq m. Sieve area: 6.32sq m.

| | | | | | |
|-----------------|---------|-----|---------|-------|-----------|
| C7206 Farm-Line | 224,200 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |
| C7206 Top-Line | 229,600 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |
| C7206 Balance | 246,100 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |

7200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers – 8.8sq m. Sieve area: 6.32sq m.

| | | | | | |
|--------------------|---------|-----|---------|-------|-----------|
| C7206 TS Farm-Line | 238,400 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |
| C7206 TS Top-Line | 243,800 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |
| C7206 TSB Balance | 260,300 | 6.3 | 5.4-9.0 | 9,500 | M-B 340hp |

9200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 7.36sq m. Sieve area: 5.28sq m.

| | | | | | |
|-----------|---------|-----|---------|-------|-----------|
| C9205 TS | 233,000 | 6.3 | 4.8-7.2 | 9,500 | M-B 340hp |
| C9205 TSB | 249,500 | 6.3 | 4.8-7.2 | 9,500 | M-B 340hp |

9200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers – 8.8sq m. Sieve area: 6.32sq m.

| | | | | | |
|-----------|---------|-----|---------|-------|-----------|
| C9206 TS | 265,700 | 7.2 | 5.4-9.0 | 9,500 | M-B 395hp |
| C9206 TSB | 282,200 | 7.2 | 5.4-9.0 | 9,500 | M-B 395hp |

Note: HTS and TS – Turbo Separator with concave adjustable out of work for dry, brittle conditions; Balance and TSB – automatic 20% lateral, 6% fore-aft self-levelling chassis. Agrosky auto steering optional on C7200 and C9200 ranges. Distributor: SDF UK.

Fendt

E Series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 6.72sq m. Sieve area: 4.67sq m.

| | | | | | |
|-------|---------|--------|----------------------|-------|------------|
| 5185E | 133,350 | 4.2 FF | 4.8-6.0 FF | 5,200 | AGCO 176hp |
| 5225E | 152,980 | 4.8 FF | 6.0-7.6 FF or 5.5 PF | 6,500 | AGCO 218hp |

L Series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 7.62sq m. Sieve area: 4.67sq m.

| | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----|----------------------|-------|------------|
| 5225L | 174,100 | 5.4 | 4.8-7.6 FF or 6.2 PF | 8,600 | AGCO 243hp |
| L Series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 7.62sq m. Sieve area: 4.67sq m. | | | | | |
| 5225L MCS | 181,420 | 5.4 | 4.8-7.6 FF or 6.2 PF | 8,600 | AGCO 243hp |

L Series Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers – 8.30sq m. Sieve area: 5.58sq m.

| | | | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-------|--------------------------|-------|------------|
| 6275L | 191,680 | 6.0FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 243hp |
| L Series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9.00sq m. Sieve area: 5.58sq m. | | | | | |
| 6275L MCS | 199,010 | 6.0FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 276hp |

C Series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers – 6.72sq m. Sieve area: 4.67sq m.

| | | | | | |
|---------------------|---------|--------|--------------------------|-------|----------------|
| 5275C | 208,410 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 9,000 | AGCO 276/306hp |
| 5275C ParaLevel 2wd | 220,810 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 276/306hp |

MACHINERY

| | | | | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------|--------------------------|--------|-----------------|
| 5275C ParaLevel 4wd | 234,120 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 276/306hp |
| C Series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m. | | | | | |
| 6335C | 226,520 | 7.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 9,000 | AGCO 320/360hp |
| 6335C ParaLevel 4wd | 250,870 | 7.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 320/360hp |
| 6335C ParaLevel Integrale 4wd | 265,450 | 6.0 FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 320/360hp |
| P Series Threshing: 1.68m x 60cm cylinder + beater + rethresher. Separation: 1.68m x 50cm peg drum + eight walkers - 10.47sq m. Sieve area: 5.30sq m. | | | | | |
| 8380P | 259,760 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 348/379hp |
| 8380P Atrak | 308,860 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 348/379hp |
| 8380P AutoLevel | 271,020 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 349/374hp |
| 8410P | 275,070 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 12,500 | AGCO 404hp |
| 8410P Atrak | 324,170 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 12,500 | AGCO 404hp |
| 8410P AutoLevel | 285,620 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 10,500 | AGCO 404hp |
| X Series Threshing: 1.7m x 60cm cylinder + beater + rotor-feeder (concave area - 1.9sq.m). Separation: Two 47.5cm x 4.2m variable speed hydro-drive rotors - 5.44sq m. Sieve area: 5.30sq m. | | | | | |
| 9490X | 335,030 | 10.74 PF | 9.2 PF | 12,500 | AGCO 466/510hp |
| 9490X Atrak | 384,130 | 10.74 PF | 9.2 PF | 12,500 | AGCO 466/510hp |
| 9490X AutoLevel | 339,100 | 9.2 PF | 10.74 PF | 10,500 | AGCO 466/510hp |
| Note: Fendt P Series combines have eight narrow straw walkers for more intensive action within equivalent area of six conventional walkers. AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Cutting tables: FF - Free Flow; PF - Power Flow with extended cutterbar position and short conveyor belt behind. Chaff spreader and Constant flow ground speed adjusting feedrate standard on P Series and X Series; yield meter /moisture sensor standard on 8410P and 9490X. Auto-Guide xls GPS auto steering option £6,030 on P Series and X Series. Atrak - 660mm traction belt on rubber block suspension undercarriage. 4wd: L Series £13,310; C Series £13,310; P Series £17,010; X Series £17,010. Distributor: Fendt UK & Ireland. | | | | | |
| S600 Series Threshing: feed drum + 76.2cm x 3.12m rotor. Separation: as for threshing - 3.0 or 3.09sq m. Sieve area: 5.20sq m. | | | | | |
| S670 ProDrive 40kph | 342,440 | 7.6 | 9.15 | 10,600 | Deere 392/449hp |
| S670 ProDrive 40kph Tracks | 391,834 | 7.6 | 9.15 | 10,600 | Deere 392/449hp |
| S670 ProDrive 40kph HillMaster | 357,112 | 7.6 | 9.15 | 10,600 | Deere 392/449hp |
| S680 ProDrive 40kph | 386,353 | 9.15 | 7.6-10.7 | 14,100 | Deere 473/540hp |
| S680 ProDrive 40kph Tracks | 435,747 | 9.15 | 7.6-10.7 | 14,100 | Deere 473/540hp |
| S680 ProDrive 40kph HillMaster | 386,729 | 9.15 | 7.6-10.7 | 10,600 | Deere 473/540hp |
| S685 ProDrive 40kph | 410,392 | 10.7 | 9.15 | 14,100 | Deere 500/570hp |
| S685 ProDrive 40kph Tracks | 459,786 | 10.7 | 9.15 | 14,100 | Deere 500/570hp |
| S685 ProDrive 40kph HillMaster | 410,688 | 10.7 | 9.15 | 10,600 | Deere 500/570hp |
| S690 ProDrive 40kph | 443,745 | 12.2 | 9.15-10.7 | 14,100 | Deere 543/617hp |
| S690 ProDrive 40kph Tracks | 493,139 | 12.2 | 9.15-10.7 | 14,100 | Deere 543/617hp |
| S690 ProDrive 40kph HillMaster | 430,576 | 10.7 | 9.15 | 10,600 | Deere 543/617hp |
| Note: Selected models available with "I" precision farming specifications, including JDLink, AutoTrac GPS auto steering and HarvestDoc crop recording. ProDrive - IVT hydrostatic transmission with auto two-speed gearbox and diff lock. HillMaster - automatic 15% chassis levelling plus 7% sieve compensation. Optional Premium Flow 7.6m, 9.15m, 10.7m and 12.2m tables have conveyor feed between forward-positioned knife and auger. Tracks - 660mm traction belt on undercarriage with hydro-pneumatic suspension. Optional 4wd: £16,000 for all models with wheels or tracks. Distributor: John Deere. | | | | | |
| Massey Ferguson | | | | | |
| MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 6.72sq m. Sieve area: 4.67sq m. | | | | | |
| 7340 | 133,350 | 4.2 FF | 4.8-6.0 FF | 5,200 | AGCO 176hp |
| 7344 | 152,980 | 4.8 FF | 6.0-7.6 FF or 5.5 PF | 6,500 | AGCO 218hp |
| MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 7.62sq m. Sieve area: 4.67sq m. | | | | | |
| 7345 S | 174,100 | 5.4 | 4.8-7.6 FF or 6.2 PF | 8,600 | AGCO 243hp |
| MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 7.62sq m. Sieve area: 4.67sq m. | | | | | |
| 7345 S MCS | 181,420 | 5.4 | 4.8-7.6 FF or 6.2 PF | 8,600 | AGCO 243hp |
| MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers - 8.30sq m. Sieve area: 5.58sq m. | | | | | |
| 7347 S | 191,680 | 6.0FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 243hp |
| MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m. | | | | | |
| 7347 S MCS | 199,010 | 6.0FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 276hp |
| MF 7300 Beta Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 6.72sq m. Sieve area: 4.67sq m. | | | | | |

| | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------|--------------------------|--------|----------------|
| 7360 | 208,410 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 9,000 | AGCO 276/306hp |
| 7360 ParaLevel 2wd | 220,810 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 276/306hp |
| 7360 ParaLevel 4wd | 234,120 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 276/306hp |
| 7360 ParaLevel Integrale 4wd | 252,260 | 6.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 276/306hp |
| MF 7300 Beta Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9.00sq m. Sieve area: 5.58sq m. | | | | | |
| 7370 | 226,520 | 7.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 9,000 | AGCO 320/360hp |
| 7370 ParaLevel 2wd | 237,560 | 7.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 320/360hp |
| 7370 ParaLevel 4wd | 250,870 | 7.0 FF | 4.8-7.6 FF or 5.4-6.8 PF | 8,600 | AGCO 320/360hp |
| 7370 ParaLevel Integrale 4wd | 265,450 | 6.0 FF | 4.8-7.6 FF or 5.4-6.2 PF | 8,600 | AGCO 320/360hp |
| MF 7300 Centora Threshing: 1.68m x 60cm cylinder + beater + rethresher. Separation: 1.68m x 50cm peg drum + eight walkers – 10.47sq m. Sieve area: 5.30sq m. | | | | | |
| 7380 | 259,760 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 348/379hp |
| 7380 Atrak | 308,860 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 348/379hp |
| 7380 AutoLevel | 271,020 | 7.7 PF | 7.6 FF or 6.8-7.6 PF | 10,500 | AGCO 349/374hp |
| 7382 | 275,070 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 12,500 | AGCO 404hp |
| 7382 Atrak | 324,170 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 12,500 | AGCO 404hp |
| 7382 AutoLevel | 285,620 | 7.7 PF | 7.6 FF or 6.8-9.2 PF | 10,500 | AGCO 404hp |
| MF 9300 Delta Threshing: 1.7m x 60cm cylinder + beater + rotor-feeder (concave area – 1.9sq.m). Separation: Two 47.5cm x 4.2m variable speed hydro-drive rotors – 5.44sq m. Sieve area: 5.30sq m. | | | | | |
| 9380 | 335,030 | 10.74 PF | 9.2 PF | 12,500 | AGCO 466/510hp |
| 9380 Atrak | 384,130 | 10.74 PF | 9.2 PF | 12,500 | AGCO 466/510hp |
| 9380 AutoLevel | 339,100 | 9.2 PF | 10.74 PF | 10,500 | AGCO 466/510hp |

Note: MF Centora models have eight narrow straw walkers for more intensive action within equivalent area of six conventional walkers. AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Cutting tables: FF – Free Flow; PF – Power Flow with extended cutterbar position and short conveyor belt behind. Chaff spreader and Constant flow ground speed adjusting feedrate standard on 7380 Centora upwards; yield meter /moisture sensor standard on MF7382 and MF9380 Delta. Auto-Guide xis GPS auto-steering option £6,030 on MF Delta and MF Centora models. Atrak – 660mm traction belt on rubber block suspension undercarriage. 4wd: MF Activa £13,310; MF Beta £13,310; MF Centora £17,010; MF Delta £17,010. Distributor: Massey Ferguson UK & Ireland.

New Holland

TC4 Threshing: 1.04m x 60cm cylinder + beater. Separation: Optional 60cm peg drum + four walkers – 4.00sq m. Sieve area: 3.27sq m.

| | | | | | |
|--------|---------|-----|-----|-------|----------|
| TC4.90 | 142,178 | 3.9 | 4.5 | 5,000 | NH 175hp |
|--------|---------|-----|-----|-------|----------|

TC5 Threshing: 1.3m x 60cm cylinder + beater. Separation: 60cm peg drum + five walkers – 5.00sq m. Sieve area: 4.13sq m.

| | | | | | |
|-------------------|---------|------|------|-------|----------|
| TC5.70 SmartSieve | 183,964 | 5.49 | 4.88 | 5,200 | NH 175hp |
| TC5.80 SmartSieve | 206,455 | 5.49 | 4.88 | 6,400 | NH 227hp |
| TC5.90 SmartSieve | 214,487 | 5.49 | 4.88 | 6,400 | NH 258hp |

CX 5000 Threshing: 1.3m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + five walkers – 7.37sq m. Sieve area: 4.32sq m.

| | | | | | |
|------------------------------|---------|------|---------|-------|----------|
| CX 5080 Elevation SmartSieve | 229,170 | 5.49 | 4.0-6.1 | 8,300 | NH 258hp |
| CX 5090 Elevation SmartSieve | 241,120 | 5.49 | 4.0-6.1 | 8,300 | NH 303hp |
| CX 5090 Elevation Laterale | 259,342 | 5.49 | 4.0-6.1 | 8,300 | NH 303hp |

CX 6000 Threshing: 1.56m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + six walkers – 8.84sq m. Sieve area: 5.21sq m.

| | | | | | |
|------------------------------|---------|------|-----|-------|-----------|
| CX 6080 Elevation SmartSieve | 254,695 | 6.1 | 7.3 | 9,300 | NH 303hp |
| CX 6090 Elevation SmartSieve | 267,398 | 7.62 | 6.1 | 9,300 | FPT 333hp |
| CX 6090 Elevation Laterale | 287,718 | 7.62 | 6.1 | 9,300 | FPT 333hp |

CX 7 Threshing: 1.3m x 75cm cylinder + 61cm beater. Separation: 75cm peg drum (2.11sq m) + five walkers – 5.56sq m. Sieve area: 5.40sq m.

| | | | | | |
|----------------------|---------|-----|-----------|--------|-----------|
| CX 7.80 SL | 282,412 | 6.1 | 5.49-7.62 | 9,000 | FPT 340hp |
| CX 7.90 SL | 294,954 | 6.7 | 5.49-7.62 | 10,000 | FPT 374hp |
| CX 7.90 SL SmartTrax | 327,926 | 6.7 | 5.49-7.62 | 10,000 | FPT 374hp |

CX 8 Threshing: 1.56m x 75cm cylinder + 61cm beater. Separation: 75cm diameter peg drum (2.54sq m) + six walkers – 6.68sq m. Sieve area: 6.50sq m.

| | | | | | |
|----------------------|---------|------|------|--------|-----------|
| CX 8.70 SL | 310,406 | 7.6 | 6.1 | 11,500 | FPT 374hp |
| CX 8.80 SL | 333,045 | 7.6 | 9.15 | 11,500 | FPT 401hp |
| CX 8.80 SL SmartTrax | 364,333 | 7.6 | 9.15 | 11,500 | FPT 401hp |
| CX 8.85 SL | 343,200 | 9.15 | 7.32 | 12,500 | FPT 450hp |
| CX 8.85 SL SmartTrax | 373,981 | 9.15 | 7.32 | 12,500 | FPT 450hp |
| CX 8.90 SL | 349,886 | 9.15 | 7.32 | 12,500 | FPT 490hp |
| CX 8.90 SL SmartTrax | 380,582 | 9.15 | 7.32 | 12,500 | FPT 490hp |

MACHINERY

CR Threshing: 450mm feed roller + two 43cm x 2.64m variable-speed rotors. Separation: threshing rotors + 1.3m x 40cm beater – 2.43sq m. Sieve area: 5.40sq m.

| | | | | | |
|-------------------|---------|------|------|--------|-----------|
| CR 7.90 | 334,702 | 7.62 | 9.15 | 11,500 | FPT 449hp |
| CR 8.80 | 365,353 | 9.15 | 7.62 | 12,500 | FPT 496hp |
| CR 8.80 SmartTrax | 407,059 | 9.15 | 7.62 | 12,500 | FPT 496hp |

CR Threshing: 450mm feed roller + two 56cm x 2.64m variable speed rotors. Separation: threshing rotors + 1.56m x 40cm beater – 3.06sq m. Sieve area: 6.50sq m.

| | | | | | |
|------------------------------|---------|------|------|--------|-----------|
| CR 8.90 | 397,936 | 9.15 | 10.7 | 12,500 | FPT 517hp |
| CR 8.90 SmartTrax | 427,911 | 9.15 | 10.7 | 12,500 | FPT 517hp |
| CR 9.80 | 433,546 | 10.7 | 12.5 | 12,500 | FPT 571hp |
| CR 9.80 SmartTrax | 467,567 | 10.7 | 12.5 | 12,500 | FPT 571hp |
| CR 9.90 SmartTrax | 509,247 | 10.7 | 12.5 | 14,500 | FPT 571hp |
| CR10.90 SmartTrax Terraglide | 569,590 | 12.5 | 10.7 | 14,500 | FPT 652hp |

Note: SmartSieve – dynamic 25% slope compensation; Laterale – 18% lateral self-levelling chassis plus SmartSieve dynamic slope compensation; SL – automatic 17% self-levelling cleaning shoe; CR and CX 7/8 models have OptiClean self-levelling cleaning shoe. VariFeed table with 575mm extending knife optional on TC5.80, TC5.90 and all CX and CR models. SmartSteer scanning laser auto-steering optional for £3,843 on all CX and CR models. SmartTrax traction belts 61cm and 76cm; SmartTrax with Terraglide suspension 61cm, 72cm and 86cm. IntelliSteer GPS auto-steering optional for £9,062 on CX7/8 and CR models. Optional 4wd: CX and CR £14,185. Distributor: New Holland Agriculture.

Versatile

RT 400 Series Threshing: Two feeder house separation drums + beater + 76cm diameter rotor. Separation: as for threshing – 5.4sq m. Sieve area: 5.20sq m.

| | | | | | |
|-------|-----|----|------|--------|---------------|
| RT490 | poa | 7m | 6-9m | 11,980 | Cummins 490hp |
|-------|-----|----|------|--------|---------------|

Note: Optional 4wd Epa Distributor: JPM Agricultural.