

Ultimate guide to buying a combine

Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
CASE-IH					
140-series Threshing: One 76cm x 2.79m three-speed variator-drive rotor. Separation: as for threshing - 2.80sq m. Sieve area: 5.52sq m.					
5140 Cross Flow	£260,101	5.48	4.88-6.70	8,810	FPT 312hp
6140 Cross Flow	£297,861	6.70	5.48-6.10	10,570	FPT 400hp
7140 Cross Flow	£329,800	7.62	6.09-9.14	10,570	FPT 449hp
250-series Threshing: One 76cm x 2.62m three-range hydro-drive rotor. Separation: as for threshing - 2.98sq m. Sieve area: 6.50sq m.					
7250	£404,062	9.14	7.62-10.7	11,100	FPT 498hp
7250 Accutrac	£453,103	9.14	7.62-10.8	11,100	FPT 498hp
8250 X-Tra	£460,212	10.7	9.14-12.5	14,440	FPT 571hp
8250 Accutrac X-Tra	£509,253	10.7	9.14-12.6	14,440	FPT 571hp
9250 X-Tra	£504,277	12.5	9.14-10.7	14,440	FPT 634hp
9250 Accutrac X-Tra	£553,318	12.5	9.14-10.7	14,440	FPT 634hp
<i>Note: X-Tra models equipped with Redekop MAV straw chopper and chaff distributor (optional on 7250) in addition to standard straw chopper. "ST" (small tube) rotor standard on all models. Prices include 3050-series table with 570mm fore-aft knife adjustment. Hydraulic side knives optional. Axial-Flow 140-series combines have Cross Flow cleaning system for hillside compensation up to 12%; 250-series have self-levelling shaker shoe assembly for 12% slope compensation. AFS AccuGuide GPS steering - 140-series £13,878; 250-series standard. Accutrac traction belt widths 61cm, 72cm and 86cm. 4wd option: 140-series £16,781; 250-series £16,781. Distributor: Case IH Agriculture.</i>					
CLAAS					
Avero 200-series Threshing: Separation drum + 1.06m x 45cm cylinder + beater. Separation: Four walkers + overhead agitator tine drum - 4.8sq m. Sieve area: 3.0sq m.					
240	£119,930	4.9 C	3.7-5.4	5,600	Perkins 205hp
Tucano 300-series Threshing: 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines - 6.78sq m. Sieve area: 4.25sq m.					
320	£139,980	6.2 V	3.7-5.4	6,500 or 7,500	M-B 245hp
Tucano 400-series Threshing: Separation drum + 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines - 7.26sq m. Sieve area: 4.7sq m.					
420	£157,000	6.2 V	4.9-6.0	7,500	M-B 245hp
430	£168,000	6.2 V	4.9-6.0	8,000 or 9,000	M-B 286hp
430 Montana	£185,000	6.2 V	4.9-6.0	8,000 or 9,000	M-B 286hp
Tucano 400-series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: Six walkers + overhead agitator tines - 8.75sq m. Sieve area: 5.65sq m.					

>





Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
440	£186,000	6.8 V	6.0-7.7	9,000	M-B 286hp
450	£197,000	7.7 V	6.0-9.3	10,000	M-B 313hp
450 Montana	£215,000	7.7 V	6.0-9.3	10,000	M-B 313hp
Tucano 500-series Threshing: Separation drum + 1.32m x 45cm cylinder + beater. Separation: One 57cm x 4.2m vari-speed rotor - n/a sq m. Sieve area: 4.7sq m.					
560	£195,000	7.7 V	6.0-9.3	9,000	M-B 381hp
560 Montana	£215,000	7.7 V	6.0-9.3	9,000	M-B 381hp
Tucano 500-series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: One 57cm x 4.2m vari-speed rotor - n/a sq m. Sieve area: 5.65sq m.					
570	£202,900	7.7 V	6.0-9.3	10,000 or 11,000	M-B 354hp
570 Montana	£220,000	7.7 V	6.0-9.3	10,000 or 11,000	M-B 354hp
580	£210,000	7.7 V	6.0-9.3	11,000	M-B 381hp
580 Montana	£225,000	7.7 V	6.0-9.3	11,000	M-B 381hp
Lexion 600-series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Five walkers + overhead agitator tine drum - 8.23sq m. Sieve area: 4.80sq m.					
620	£182,600	6.2 V	5.4-6.6	9,000	M-B 313hp
630	£189,450	6.8 V	6.0-7.7	9,000	M-B 354hp
630 Montana	£206,240	6.8 V	6.0-7.7	9,000	M-B 354hp
Lexion 600-series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Six walkers + overhead agitator tine drum - 9.85sq m. Sieve area: 5.80sq m.					
650	£213,200	7.7 V	6.0-9.3 V	10,000	M-B 354hp
660	£227,520	7.7 V	6.6-9.3 V	11,000	M-B 408hp
660 Terra Trac	£265,470	7.7 V	6.6-9.3 V	11,000	M-B 435hp
670	£238,370	9.3 V	6.6-9.3 V	11,000	M-B 435hp
670 Montana	£255,640	7.7 V	6.6-9.3 V	10,000	M-B 435hp
670 Terra Trac	£281,290	9.3 V	6.6-9.3 V	11,000	M-B 435hp
Lexion 700-series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors - 4.32sq m. Sieve area: 5.10sq m.					
740	£251,240	7.7 V	6.6-9.3 V	10,000	M-B 405hp
750	£293,230	9.3 V	6.6-9.3 V	10,000	M-B 435hp
750 Montana	£307,530	9.3 V	6.6-9.3 V	10,000	M-B 435hp
750 Terra Trac	£328,710	9.3 V	6.6-10.8 V	10,000	M-B 435hp
760	£336,190	9.3 V	7.5-10.8 V	11,000	Perkins 503hp
760 Montana	£337,450	9.3 V	7.5-9.3 V	9,000	Perkins 503hp
760 Terra Trac	£369,610	10.5 V	7.5-10.8 V	11,000	Perkins 503hp
Lexion 700-series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors - n/a sq m. Sieve area: 6.20sq m.					
770	£369,240	10.5 V	9.3-10.8 V	12,800	M-B 585hp
770 Terra Trac	£413,260	12.3 V	9.3-12.3 V	12,800	M-B 585hp
780 Terra Trac	£453,620	12.3 V	10.5-12.3 V	13,500	M-B 625hp

Note: 40kph transmission optional on Lexion 750 Terra Trac and 760 Terra Trac. Montana - automatic chassis levelling 17% lateral, 6% fore-aft. 4-D dynamic sieve 20% slope compensation standard on Lexion 760, 770 and 780, optional on all other models. Laser Pilot laser-scanning autosteer system standard on Lexion 760, 770 and 780, optional on other models. GPS Pilot satellite-guided autosteer optional on all models. Cemos settings advice system and Cemos Automatic optional on all Lexion 600- and 700-series combines. Terra Trac - rubber track suspension undercarriage with 635mm, 735mm or 890mm traction belts. Cutting tables: C - Contour, AC - Auto Contour, V - Auto Contour Vario (with fore-aft knife adjustment). Cruise Pilot automatic forward speed control optional on Lexion 780 - 650. 4wd optional on all models. Distributor: Claas UK.

DEUTZ-FAHR

6000-series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers - 5.28sq m. Sieve area: 4.22sq m.					
6205 Farm-Line	£165,115	4.8	3.6-5.4	7,000	M-B 250hp
6205 Top-Line	£172,616	4.8	3.6-5.4	7,000	M-B 250hp
6000-series Threshing: 1.27m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers - 5.28sq m. Sieve area: 4.22sq m.					
6205 HTS Farm-Line	£173,777	4.8	3.6-5.4	7,000	M-B 250hp
6205 HTS Top-Line	£181,278	4.8	3.6-5.4	7,000	M-B 250hp
7000-series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers - 7.36sq m. Sieve area: 5.28sq m.					
C7205 Farm-Line	£215,390	5.4	4.2-7.2	8,500	M-B 288/309hp
C7205 Farm-Line Tracks	poa	5.4	4.2-7.2	8,500	M-B 288/309hp
C7205 Top-Line	£219,319	5.4	4.2-7.2	8,500	M-B 288/309hp
C7205 Top-Line Tracks	poa	5.4	4.2-7.2	8,500	M-B 288/309hp
7000-series Threshing: 1.27m x 60cm cylinder+ beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers - 7.36sq m. Sieve area: 5.28sq m.					
C7205 TS Farm-Line	£228,116	6.3	4.8-7.2	8,500	M-B 288/309hp



<	Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
	C7205 TS Farm-Line Tracks	poa	6.3	4.8-7.2	8,500	M-B 288/309hp
	C7205 TS Top-Line	£232,938	6.3	4.8-7.2	8,500	M-B 288/309hp
	C7205 TS Top-Line Tracks	poa	6.3	4.8-7.2	8,500	M-B 288/309hp
	C7205 TSB Balance	£251,513	6.3	4.8-7.2	8,500	M-B 288/309hp
	7000-series Threshing: 1.52m x 60cm cylinder + beater. Separation: Six walkers - 8.8sq m. Sieve area: 6.32sq m.					
	C7206 Farm-Line	£251,424	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 Farm-Line Tracks	poa	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 Top-Line	£257,407	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 Top-Line Tracks	poa	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 Balance	£275,892	6.3	5.4-9.0	9,500	M-B 320/340hp
	7000-series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers - 8.8sq m. Sieve area: 6.32sq m.					
	C7206 TS Farm-Line	£267,319	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 TS Farm-Line Tracks	poa	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 TS Top-Line	£273,302	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 TS Top-Line Tracks	poa	6.3	5.4-9.0	9,500	M-B 320/340hp
	C7206 TS Balance	£291,787	6.3	5.4-9.0	9,500	M-B 320/340hp
	9000-series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers - 7.36sq m. Sieve area: 5.28sq m.					
	C9305 TS	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	C9305 TS 4wd	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	C9305 TS Tracks	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	C9305 TS Tracks 4wd	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	C9305 TS Balance	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	C9305 TS Balance 4wd	tbc	6.3	4.8-7.2	10,500	M-B 354hp
	9000-series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers - 8.8sq m. Sieve area: 6.32sq m.					
	C9306 TS	£307,593	7.2	5.4-9.0	10,500	M-B 363/395hp
	C9306 TS 4wd	poa	7.2	5.4-9.0	10,500	M-B 363/395hp
	C9306 TS Tracks	poa	7.2	5.4-9.0	10,500	M-B 363/395hp
	C9306 TS Tracks 4wd	poa	7.2	5.4-9.0	10,500	M-B 363/395hp
	C9306 TS Balance	£326,792	7.2	5.4-9.0	10,500	M-B 363/395hp
	C9306 TS Balance 4wd	poa	7.2	5.4-9.0	10,500	M-B 363/395hp
	<i>Note: HTS and TS - Turbo Separator with concave adjustable out of work for dry, brittle conditions. TSB Balance - automatic 20% lateral, 6% fore-aft self-levelling chassis; TSXB Balance available to special order with rear axle lift for 22% lateral, 28% uphill, 5% downhill self-levelling. Agrosky autosteering optional on C7000 and C9000 ranges. Distributor: SDF UK.</i>					
	FENDT					
	E-series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 6.72sq m. Sieve area: 4.67sq m.					
	5185E	£143,430	4.2 FF	4.8-6.0 FF	5,200	AGCO 176hp
	5225E	£164,150	4.8 FF	6.0-7.6 FF or 5.5 PF	6,500	AGCO 218hp
	L-series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 7.62sq m. Sieve area: 4.67sq m.					
	5225L	£187,950	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	L-series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 7.62sq m. Sieve area: 4.67sq m.					
	5225L MCS	£194,760	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	5225L MCS ParaLevel	£230,270	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	L-series Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers - 8.30sq m. Sieve area: 5.58sq m.					
	6275L	£206,810	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
	L-series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m.					
	6275L MCS	£213,630	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
	6275L MCS ParaLevel 4wd	£249,130	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
	C-series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 6.72sq m. Sieve area: 4.67sq m.					
	5275C	£223,760	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 276/306hp
	5275C ParaLevel 2wd	£236,840	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
	5275C ParaLevel 4wd	£251,460	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
	C-series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m.					
>						

<	Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
	6335C	£247,440	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
	6335C Atrak	£287,580	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
	6335C ParaLevel 4wd	£273,670	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 320/360hp
	6335C ParaLevel Integrale 4wd	£285,220	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 320/360hp
	Ideal Threshing: 4.85m x 60cm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 7.45sq m.					
	Ideal 7	£482,960	9.20m PF	7.70-10.70m PF	12,500 or 17,100	AGCO 451hp
	Ideal 7 ParaLevel	£499,880	9.20m PF	7.70-10.70m PF	12,500	AGCO 451hp
	Ideal 7 TrakRide	£530,030	9.20m PF	7.70-10.70m PF	12,500 or 17,100	AGCO 451hp
	Ideal Threshing: 2 x 4.85m x 60cm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 7.45sq m.					
	Ideal 8	£530,780	10.70m PF	9.20-12.20m PF	12,500 or 17,100	MAN 538hp
	Ideal 8 ParaLevel	£547,090	10.70m PF	9.20-12.20m PF	12,500	MAN 538hp
	Ideal 8 TrakRide	£583,050	10.70m PF	9.20-12.20m PF	12,500 or 17,100	MAN 538hp
	Ideal Threshing: 2 x 4.85m x 60cm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 7.95sq m.					
	Ideal 9	£595,740	12.20m PF	9.20-12.20m PF	17,100 or 12,500	MAN 647hp
	Ideal 9 ParaLevel	£607,050	12.20m PF	9.20-12.20m PF	12,500	MAN 647hp
	Ideal 9 TrakRide	£648,010	12.20m PF	9.20-12.20m PF	17,100 or 12,500	MAN 647hp
	<i>Note: AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Boost power on L Series models available when unloading. Cutting tables: FF - Free Flow; PF - Power Flow and SF - Super Flow with extended cutterbar position and short conveyor belt behind. Ground speed adjusting feedrate control optional on Ideal models with 12.2m Super Flow table. Yield meter/moisture sensor - E and L Series not available; C Series optional; Ideal models standard with mapping optional. AutoGuide auto steering option £6,210. TrakRide - 660mm traction belt on rubber block suspension undercarriage; TrakRide - 610mm, 760mm and 910mm traction belts with hydraulic suspension. 4wd: L Series £13,980; C Series £13,980; Ideal AllDrive £17,730. Distributor: Fendt UK & Ireland.</i>					
	JOHN DEERE					
	W300-series Threshing: 1.11m x 50cm cylinder + 40cm diameter pre-threshing drum. Separation: Five walkers + optional overhead agitator tine drum - 4.80sq m. Sieve area: 3.40sq m.					
	W330 PTC	£179,433	4.5 300R	4.2-5.1	5,400	AGCO 201/210hp
	W400-series Threshing: 1.33m x 50cm cylinder. Separation: Six walkers + optional overhead agitator tine drum - 6.40sq m. Sieve area: 4.50sq m.					
	W440	£189,464	4.9 600R	5.1-6.7	6,000	AGCO 234/249hp
	W400-series Threshing: 1.33m x 50cm cylinder + 40cm diameter pre-threshing drum. Separation: Six walkers + optional overhead agitator tine drum - 6.40sq m. Sieve area: 4.50sq m.					
	W440 PTC	£203,039	5.5 600R	4.9-6.7	7,600	AGCO 234/249hp
	W500-series Threshing: 1.4m x 66cm cylinder + 40cm diameter beater. Separation: Five walkers + overhead agitator tine drum - 6.70sq m. Sieve area: 5.20sq m.					
	W540	£227,019	6.1 600R	4.9-7.6	8,000 or 10,000	Deere 255/277hp
	W540 HillMaster	£240,279	6.1 600R	4.9-7.6	8,000	Deere 255/277hp
	W550	£238,619	6.7 600R	4.9-7.6	8,000 or 10,000	Deere 300/330hp
	W550 HillMaster	£252,667	6.7 600R	4.9-7.6	8,000	Deere 300/330hp
	W600-series Threshing: 1.67m x 66cm cylinder + 40cm diameter beater. Separation: Six walkers + overhead agitator tine drum - 8.0sq m. Sieve area: 6.30sq m.					
	W650	£266,848	7.6 600R	4.9-9.15	9,000 or 11,000	Deere 343/377hp
	W650 ProDrive	£287,380	7.6 600R	4.9-9.15	9,000 or 11,000	Deere 343/377hp
	W650 HillMaster	£284,900	7.6 600R	4.9-9.15	9,000	Deere 343/377hp
	W660	£271,570	7.6 600R	4.9-9.15	9,000 or 11,000	Deere 382/416hp
	W660 ProDrive 40kph	£295,959	7.6 600R	4.9-9.15	9,000 or 11,000	Deere 382/416hp
	W660 HillMaster 40kph	£308,962	7.6 600R	4.9-9.15	9,000 or 11,000	Deere 382/416hp
	T500-series Threshing: 1.4m x 66cm cylinder + 40cm diameter beater. Separation: 14cm stripper roller + 50cm overshot beater + 80cm separator drum + 40cm beater (3.30sq m) + five walkers - 4.80sq m. Sieve area: 5.20sq m.					
	T550	£317,671	6.7 600R	6.1-7.6	8,000 or 10,000	Deere 300/330hp
	T550 HillMaster	£331,475	6.7 600R	6.1-7.6	8,000	Deere 300/330hp
	T560	£309,580	7.6 600R	6.1-7.6	10,000	Deere 382/416hp
	T560 ProDrive	£358,512	7.6 600R	6.1-7.6	10,000	Deere 382/416hp
	T560 ProDrive HillMaster	£373,684	7.6 600R	6.1-9.15	10,000	Deere 382/416hp
	T560 ProDrive Tracks	£409,364	7.6 600R	6.1-9.15	10,000	Deere 382/416hp
	T600-series Threshing: 1.67m x 66cm cylinder + 40cm diameter beater. Separation: 14cm stripper roller + 50cm overshot beater + 80cm separator drum + 40cm beater (4.0sq m) + six walkers - 5.80sq m. Sieve area: 6.30sq m.					
	T660	£322,170	9.15 600R	6.1-10.7	9,000 or 11,000	Deere 382/416hp
	T660 ProDrive	£340,339	9.15 600R	6.1-10.7	9,000 or 11,000	Deere 382/416hp
	T660 ProDrive HillMaster	£358,544	9.15 600R	6.1-10.7	9,000 or 11,000	Deere 382/416hp

>

<	Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
	T660 ProDrive Tracks	£396,506	9.15 600R	6.1-10.7	9,000 or 11,000	Deere 382/416hp
	T670	£345,654	9.15 600R	6.1-10.7	11,000	Deere 449/483hp
	T670 ProDrive	£363,883	9.15 600R	6.1-10.7	11,000	Deere 449/483hp
	T670 ProDrive HillMaster	£380,423	9.15 600R	6.1-10.7	11,000	Deere 449/483hp
	T670 ProDrive Tracks	£417,045	9.15 600R	6.1-10.7	11,000	Deere 449/483hp
	S700-series Threshing: feed drum + 76.2cm x 3.12m rotor. Separation: rotor diameter increased to 838mm - 3.0 or 3.09sq m. Sieve area: 5.20sq m.					
	S770	£375,625	9.15 600R	7.6	10,600	Deere 391/449hp
	S770 ProDrive	£385,622	9.15 600R	7.6	10,600	Deere 391/449hp
	S770 ProDrive Tracks	£436,908	9.15 600R	7.6	10,600	Deere 391/449hp
	S770 ProDrive HillMaster	£404,925	9.15 600R	7.6	10,600	Deere 391/449hp
	S780 ProDrive	£430,938	9.15 600R	7.6-10.7	14,100	Deere 473/540hp
	S780 ProDrive Tracks	£482,184	9.15 600R	7.6-10.7	14,100	Deere 473/540hp
	S780 ProDrive HillMaster	£440,932	9.15 600R	n/a	10,600	Deere 473/540hp
	S785 ProDrive	£448,902	10.7 600R	7.6-12.2	14,100	Deere 500/570hp
	S785 ProDrive Tracks	£500,148	10.7 600R	7.6-12.2	14,100	Deere 500/570hp
	S785 ProDrive HillMaster	£450,612	9.15 600R	n/a	10,600	Deere 500/570hp
	S790 ProDrive	£468,100	12.2 600R	7.6-12.2	14,100	Deere 543/617hp
	S790 ProDrive Tracks	£519,346	12.2 600R	7.6-12.2	14,100	Deere 543/617hp
	S790 ProDrive HillMaster	£468,677	9.15 600R	n/a	10,600	Deere 543/617hp
	<i>Note: Selected models available with 'i' precision farming specifications, including JDLink, AutoTrac GPS auto steering and HarvestDoc crop recording. ProDrive - 40kph IVT hydrostatic transmission with auto two-speed gearbox and diff lock. HillMaster - automatic 15% chassis levelling plus 7% sieve compensation. Front end options - 600R conventional; 600PF and 700PF (Premium Flow) with belt feed between forward-positioned knife and auger; 600X with 800mm of hydraulic fore-aft knife positioning; 700D (not for HillMaster models) belt centre-feeding table. Tracks - 610mm or 762mm traction belt on undercarriage with hydro-pneumatic suspension. Optional 4wd: £18,239 for all models with wheels or tracks. Distributor: John Deere.</i>					
	MASSEY FERGUSON					
	MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 6.72sq m. Sieve area: 4.67sq m.					
	7340	£146,670	4.8 FF	4.2-6.0 FF	5,200	AGCO 176hp
	7344	£164,150	4.8 FF	6.0-7.6 FF or 5.5 PF	6,500	AGCO 218hp
	MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers - 7.62sq m. Sieve area: 4.67sq m.					
	7345 S	£187,950	5.4 FF	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 7.62sq m. Sieve area: 4.67sq m.					
	7345 S MCS	£207,340	5.4 PF	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	7345 S MCS ParaLevel 2wd	£242,850	5.4 PF	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	7345 S MCS ParaLevel 4wd	£224,690	5.4 PF	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
	MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers - 8.30sq m. Sieve area: 5.58sq m.					
	7347 S	£206,810	5.8 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 243hp
	MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m.					
	7347 S MCS	£225,760	6.0 PF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276hp
	7347 S MCS ParaLevel 4wd	£261,260	6.0 PF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
	MF 7300 Beta Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers - 6.72sq m. Sieve area: 4.67sq m.					
	7360	£235,890	6.0 PF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 276/306hp
	7360 ParaLevel 2wd	£249,250	6.0 PF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
	7360 ParaLevel 4wd	£263,590	6.0 PF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
	7360 ParaLevel Integrale 4wd	£283,130	6.0 PF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
	MF 7300 Beta Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers - 9.00sq m. Sieve area: 5.58sq m.					
	7370	£243,160	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
	7370 Atrak	£293,600	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
	7370 ParaLevel 4wd	£279,220	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 320/360hp
	7370 ParaLevel Integrale 4wd	£298,770	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 320/360hp
	Ideal Threshing: 4.85m x 60cm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 7.45sq m.					
	Ideal 7	£390,790	9.1 SF	7.7-10.7 PF	12,500 or 17,100	AGCO 451hp
	Ideal 7 ParaLevel	£404,890	9.1 SF	7.7-10.7 PF	12,500 or 17,100	AGCO 451hp
	Ideal 7 Trak Ride	£430,020	9.1 SF	7.7-10.7 PF	12,500 or 17,100	AGCO 451hp

>

Model	List price - £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make and max harvesting power/max unloading power (hp)
Ideal Threshing: 2 x 4.85m x 60cm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 7.45sq m.					
Ideal 8	£432,170	10.6 SF	9.2-12.2 PF	12,500 or 17,100	MAN 538hp
Ideal 8 ParaLevel	£445,770	10.6 SF	9.2-12.2 PF	12,500 or 17,100	MAN 538hp
Ideal 8 Trak Ride	£475,730	10.6 SF	9.2-12.2 PF	12,500 or 17,100	MAN 538hp
Ideal Threshing: 2 x 4.85m x 60cm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 7.95sq m.					
Ideal 9	£487,300	12.2 SF	9.2-12.2 PF	17,100 or 12,500	MAN 647hp
Ideal 9 ParaLevel	£496,730	12.2 SF	9.2-12.2 PF	17,100 or 12,500	MAN 647hp
Ideal 9 Trak Ride	£530,860	12.2 SF	9.2-12.2 PF	17,100 or 12,500	MAN 647hp
Note: AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Boost power on Beta models available when unloading. Cutting tables: FF - Free Flow; PF - Power Flow and SF - Super Flow with extended cutterbar position and short conveyor belt behind. Ground speed adjusting feedrate control optional on Ideal models with 12.2m Super Flow table. Yield meter/moisture sensor - MF7340 and MF 7344 not available; MF7345 S and MF7347 S optional; all Beta models optional; Ideal models standard with mapping optional. AutoGuide auto steering option for Beta and Ideal models £6,210. Atrak - 660mm traction belt on rubber block suspension undercarriage; Trak Ride - 610mm, 760mm and 910mm traction belts with hydraulic suspension. 4wd: Activa £13,980; Beta £13,980; Ideal AllDrive £17,730. Distributor: Massey Ferguson UK & Ireland.					
NEW HOLLAND					
TC 4 Threshing: 1.04m x 60cm cylinder + beater. Separation: 60cm peg drum + four walkers - 4.00sq m. Sieve area: 3.27sq m.					
TC 4.90	£141,221	3.9	4.5	5,000	NH 175hp
TC 5 Threshing: 1.3m x 60cm cylinder + beater. Separation: 60cm peg drum + five walkers - 5.00sq m. Sieve area: 4.13sq m.					
TC 5.70 SmartSieve	£168,342	5.49	4.88	5,200	NH 175hp
TC 5.90 SmartSieve	£179,504	5.49	4.88	6,400	NH 258hp
CX 5 Threshing: 1.3m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + five walkers - 7.37sq m. Sieve area: 4.32sq m.					
CX 5.80	£223,562	6.10	5.18-6.70	8,300	NH 258hp
CX 5.90	£234,707	6.70	6.10	8,300	NH 300hp
CX 5.90 Laterale	£256,122	6.70	6.10	8,300	NH 300hp
CX 6 Threshing: 1.56m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + six walkers - 8.84sq m. Sieve area: 5.21sq m.					
CX 6.80	£250,220	6.10	7.32	9,300	NH 303hp
CX 6.90	£263,386	7.62	6.10	9,300	FPT 340hp
CX 6.90 Laterale	£282,844	7.62	6.10	9,300	FPT 340hp
CX 7 Threshing: 1.3m x 75cm cylinder + 61cm beater. Separation: 75cm peg drum (2.11sq m) + five walkers - 5.56sq m. Sieve area: 5.40sq m.					
CX 7.80 SL	£274,610	6.10	5.49-7.62	9,000	FPT 340hp
CX 7.90 SL	£286,822	6.70	5.49-7.62	10,000	FPT 374hp
CX 7.90 SL SmartTrax	£321,817	6.70	5.49-7.62	10,000	FPT 374hp
CX 8 Threshing: 1.56m x 75cm cylinder + 61cm beater. Separation: 75cm diameter peg drum (2.54sq m) + six walkers - 6.68sq m. Sieve area: 6.50sq m.					
CX 8.70 SL	£301,580	7.6	6.10	11,500	FPT 374hp
CX 8.80 SL	£324,826	7.6	9.15	11,500	FPT 401hp
CX 8.80 SL SmartTrax	£360,814	7.6	9.15	11,500	FPT 401hp
CX 8.90 SL	£335,549	9.15	7.32	12,500	FPT 490hp
CX 8.90 SL SmartTrax	£369,096	9.15	7.32	12,500	FPT 490hp
CR Threshing: 450mm feed roller + two 43cm x 2.64m variable-speed rotors. Separation: threshing rotors + 1.3m x 40cm beater - 2.43sq m. Sieve area: 5.40sq m.					
CR 7.80 Revelation	£327,991	7.62	9.15	9,500	FPT 415hp
CR 7.90 Revelation	£347,226	7.62	9.15	11,500	FPT 460hp
CR 8.80 Revelation	£367,011	9.15	7.62	12,500	FPT 517hp
CR 8.80 Revelation SmartTrax	£412,651	9.15	7.62	12,500	FPT 517hp
CR Threshing: 450mm feed roller + two 56cm x 2.64m variable speed rotors. Separation: threshing rotors + 1.56m x 40cm beater - 3.06sq m. Sieve area: 6.50sq m.					
CR 8.90 Revelation	£392,015	9.15	10.7	12,500	FPT 517hp
CR 8.90 Revelation SmartTrax	£428,164	9.15	10.7	12,500	FPT 517hp
CR 9.80 Revelation	£427,017	10.7	12.5	12,500	FPT 571hp
CR 9.80 Revelation SmartTrax	£467,279	10.7	12.5	12,500	FPT 571hp
CR 9.90 Revelation SmartTrax	£494,884	10.7	12.5	14,500	FPT 571hp
CR10.90 Revelation SmartTrax Terraglide	£566,507	12.5	10.7	14,500	FPT 700hp
Note: SmartSieve - dynamic 25% slope compensation; Laterale - 18% lateral self-levelling chassis plus SmartSieve dynamic slope compensation; SL - automatic 17% self-levelling cleaning shoe; CX 7/8 and CR models have OptiClean self-levelling cleaning shoe. VariFeed table with 575mm extending knife optional on all models. OptiSpeed variable speed straw walkers standard on CX combines. SmartSteer scanning laser auto steering optional for £3,843 on all CX and CR models. IntelliSteer GPS auto steering optional for £9,062 on CX7/8 and CR models. SmartTrax traction belts 61cm and 76cm; SmartTrax with Terraglide suspension 61cm, 72cm and 86cm. Optional 4wd: CX and CR £14,185. Distributor: New Holland Agriculture.					