

Latest combine updates and full specifications

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
CASE IH					
150-series Threshing: one 760mm x 2.79m three-speed variator drive rotor. Separation: as for threshing – 2.80sq m. Sieve area: 5.52sq m.					
5150 X-Flow	£310,716	5.48m 3050	4.88- 6.70m	8,810	FPT 312hp
6150 X-Flow	£322,041	6.70m 3050	5.48-6.10m	10,570	FPT 400hp
7150 X-Flow	£369,358*	8.50m 3050	6.09-9.14m	10,570	FPT 453hp
<i>Note: 7150 X-Flow price include trailer for 7.62m 3050-series cutting table</i>					
250-series Threshing: one 760mm x 2.62m three-range hydro-drive rotor. Separation: as for threshing – 2.98sq m. Sieve area: 6.50sq m.					
7250	£428,310*	9.14m 3050	8.50-10.70m	11,100	FPT 498hp
7250 X-Tra	£453,597*	9.14m 3050	8.50-10.70m	11,100	FPT 498hp
7250 Accutrac	£479,382*	9.14m 3050	8.50-10.70m	11,100	FPT 498hp
7250 X-Tra Accutrac	£504,669*	9.14m 3050	8.50-10.70m	11,100	FPT 498hp
8250 X-Tra	£513,647*	10.70m 3050	9.14-12.50m	14,440	FPT 571hp
8250 Accutrac X-Tra	£562,587*	10.70m 3050	9.14-12.60m	14,440	FPT 571hp
9250 X-Tra	£567,258*	12.50m 3050	9.14-10.70m	14,440	FPT 634hp
9250 Accutrac X-Tra	£616,198*	12.50m 3050	9.14-10.70m	14,440	FPT 634hp
<i>Note: Axial-Flow 250-series prices include cutting table trailer: 9.14m £16,164; 10.70m £16,680; 12.50m £19,329. X-Tra models equipped with Redekop MAV straw chopper and chaff distributor (£2,5219 option on 7250) in addition to standard straw chopper. 'ST' (small tube) rotor standard on all models. Prices include 3050-series table with 570mm fore-aft knife adjustment. Hydraulic side knives optional. Axial-Flow 150-series combines have X-Flow cleaning system for hillside compensation up to 12%; 250-series have self-levelling shaker shoe assembly for 12% slope compensation. AFS AccuGuide GPS steering - 150-series £14,581; 250-series standard. Accutrac traction belt widths 61cm, 72cm and 86cm. Four-wheel-drive option for all models £18,161. Distributor: Case IH Agriculture.</i>					
CLAAS			NEW LEXION 5000/6000-SERIES		
Avero 200-series Threshing: 1.06m x 450mm cylinder. Separation: acceleration/separation drum ahead of threshing cylinder, beater, four walkers and overhead agitator tine drum – 4.8sq m. Sieve area: 3.0sq m.					
240	£126,380	4.90m C	3.70-5.40m	5,600	Cummins 213hp
Tucano 300-series Threshing: 1.32m x 450mm cylinder. Separation: Beater and five walkers with overhead agitator tines – 6.78 sq m. Sieve area: 4.25sq m.					
320	£147,500	6.20m V	3.70-5.40m	6,500 or 7,500	M-B 245hp
Tucano 400-series Threshing: 1.32m x 450mm cylinder. Separation: acceleration/separation drum ahead of threshing cylinder, beater, five walkers and overhead agitator tines – 7.26sq m. Sieve area: 4.7sq m.					
420	£165,430	6.20m V	4.90-6.00m	7,500	M-B 245hp
430	£177,020	6.20m V	4.90-6.00m	8,000 or 9,000	M-B 286hp
430 Montana	£194,940	6.20m V	4.90-6.00m	8,000 or 9,000	M-B 286hp
Tucano 400-series Threshing: 1.58m x 450mm cylinder. Separation: acceleration/separation drum ahead of threshing cylinder, beater, six walkers and overhead agitator tines – 8.75sq m. Sieve area: 5.65sq m.					
440	£195,990	6.80m V	6.00-7.70m	9,000	M-B 286hp
450	£207,580	7.70m V	6.00-9.30m	10,000	M-B 313hp
450 Montana	£226,550	7.70m V	6.00-9.30m	10,000	M-B 313hp
Tucano 500-series Threshing: 1.32m x 450mm cylinder. Separation: acceleration/separation drum ahead of threshing cylinder, beater and one 57cm x 4.2m variable speed rotor – n/a sq m. Sieve area: 4.7sq m.					
560	£205,470	7.70m V	6.00-9.30m	9,000	M-B 381hp
560 Montana	£226,550	7.70m V	6.00-9.30m	9,000	M-B 381hp
Tucano 500-series Threshing: 1.58m x 450mm cylinder. Separation: acceleration/separation drum ahead of threshing cylinder, beater and one 57cm x 4.2m variable speed rotor - n/a sq m. Sieve area: 5.65sq m.					
570	£213,800	7.70m V	6.00-9.30m	10,000 or 11,000	M-B 354hp
570 Montana	£231,820	7.70m V	6.00-9.30m	10,000 or 11,000	M-B 354hp
580	£221,280	7.70m V	6.00-9.30m	11,000	M-B 381hp
580 Montana	£237,090	7.70m V	6.00-9.30m	11,000	M-B 381hp
Lexion 600-series					DISCONTINUED
Lexion 5000-series Threshing: 1.42m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, 600mm peg drum, beater and five walkers – 5.40sq m. Sieve area: 5.10sq m.					
5300	£211,650	6.20m Vario	5.40m-6.60m C	10,000 or 9,000	M-B 313hp

Claas Lexion 6700 is available on wheels or tracks with a choice of 30kph or 40kph travel speeds



CLAAS/FENDT

The Fendt Ideal 10T introduction brings more performance and unique joystick steering for all Ideal models with TrakRide tracked running gear



Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
5400	£219,600	6.80m Vario	6.00m-7.70m C	10,000	M-B 354hp
5500 Terra Trac	£279,790	6.80m Vario	6.00m-9.30m C	11,000 or 10,000	M-B 408hp
Lexion 6000-series Threshing: 1.70m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, 600mm peg drum, beater and six walkers - 6.37sq m. Sieve area: 6.20sq m.					
6600	£247,160	7.70m Vario	6.60-9.30m V	10,000 or 9,000	M-B 354hp
6700	£263,580	9.30m Vario	6.60-9.30m V	11,000 or 10,000	M-B 408hp
6700 Terra Trac	£298,740	9.30m Vario	6.60-9.30m V	11,000 or 10,000	M-B 408hp
6800	£276,150	9.30m Vario	6.60-10.8m V	12,500 or 11,000	M-B 462hp
6800 Terra Trac	£326,040	9.30m Vario	6.60-10.8m V	12,500 or 11,000	M-B 462hp
6900	£288,710	9.30m Vario	6.60-10.8m V	13,500 or 12,000	MAN 507hp
6900 Terra Trac	£340,860	9.30m Vario	6.60-10.8m V	13,500 or 12,000	MAN 507hp
Lexion 700-series DISCONTINUED					
Lexion 7000-series Threshing: 1.42m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, feed drum and two 44.5cm x 4.2m variable-speed rotors - 3.00sq m (total including APS 4.69sq m). Sieve area: 5.10sq m.					
7400	£282,730	7.70m V	6.60-9.30m V	10,000	M-B 408hp
7500	£329,980	9.30m V	6.60-9.30m V	10,000	M-B 462hp
7500 Terra Trac	£369,910	9.30m V	6.60-10.80m V	11,000	M-B 462hp
7600	£378,320	9.30m V	7.50-10.80m V	11,000	MAN 507hp
7600 Terra Trac	£415,940	10.50m V	7.50-10.80m V	12,500	MAN 507hp
7700	£387,020	10.50m V	9.30-10.80m V	12,500	MAN 549hp
7700 Terra Trac	£426,610	12.30m V	9.30-12.30m V	13,500	MAN 549hp
Lexion 8000-series Threshing: 1.70m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, feed drum and two 44.5cm x 4.2m variable-speed rotors - 3.60sq m (total including APS 5.62sq m). Sieve area: 6.20sq m.					
8700	£415,520	12.30m V	10.50-12.30m V	12,500	M-B 585hp
8700 Terra Trac	£465,050	12.30m V	10.50-12.30m V	13,500	M-B 585hp
8800 Terra Trac	£510,470	12.30m V	10.80-13.80m V	15,000	M-B 653hp
8900 Terra Trac	£532,440	13.80m V	10.80-13.80m V	18,000	MAN 790hp

Note: Dynamic Power on all Lexion models regulates power output for field and road includes 40kph transmission. Tucano Montana - 430 and 560 chassis self-levelling up to 18%, 450 and 570 up to 16%. Tucano level land - optional 3D sieve lateral movement compensation for side slopes up to 20%. Lexion - 3-D dynamic sieve action optional on Lexion 5000 and 6000 Series. 4-D dynamic sieve action and rotor cage flap control for up to 20% slope compensation standard on Lexion 7600, 7700, 8800 and 8900, optional on all other models. Laser Pilot laser-scanning auto steer system standard on Lexion 7600, 7700, 8700, 8800 and 8900, optional on other models. GPS Pilot satellite-guided auto steer optional on all models. Cemos Dialog settings advice system and Cemos Automatic optional on all models. Terra Trac - rubber track suspension undercarriage with 635mm, 735mm or 890mm traction belts. Cutting tables: C - Contour, AC - Auto Contour, V - Auto Contour Vario (with fore-aft knife adjustment). Cruise Pilot automatic forward speed control optional on all models. Four-wheel drive: Optional on all models. Distributor: Claas UK.

DEUTZ-FAHR			SIMPLIFIED RANGE		
C5000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater and five walkers - 4.22sq m. Sieve area: 4.22sq m.					
5305 Farm-Line	£140,468	4.20m	3.60-4.80m	4,600	Deutz 175hp

ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
C6000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater and five walkers – 5.28sq m. Sieve area: 4.22sq m.					
6205 Farm-Line	£173,330	4.80m	3.60-5.40m	7,000	M-B 250hp
6205 Top-Line	£181,189	4.80m	3.60-5.40m	7,000	M-B 250hp
C6000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and five walkers – 5.28sq m. Sieve area: 4.22sq m.					
6205 HTS Farm-Line	£182,350	4.80m	3.60-5.40m	7,000	M-B 250hp
6205 HTS Top-Line	£190,209	4.80m	3.60-5.40m	7,000	M-B 250hp
C7000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater and five walkers – 7.36sq m. Sieve area: 5.28sq m.					
C7205 Top-Line	£239,234	5.40m	4.20-7.20m	8,500	M-B 288/309hp
C7000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and five walkers – 7.36sq m. Sieve area: 5.28sq m.					
C7205 TS Top-Line	£252,808	6.30m	4.80-7.20m	8,500	M-B 288/309hp
C7205 TSB Balance	£272,543	6.30m	4.80-7.20m	8,500	M-B 288/309hp
C7000-series Threshing: 1.52m x 600mm cylinder. Separation: Beater and six walkers – 8.8sq m. Sieve area: 6.32sq m.					
C7206 Top-Line	£278,169	6.30m	5.40-9.00m	9,500	M-B 320/340hp
C7206 Balance	£294,957	6.30m	5.40-9.00m	9,500	M-B 320/340hp
C7000-series Threshing: 1.52m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and six walkers – 8.8sq m. Sieve area: 6.32sq m.					
C7206 TS Top-Line	£295,315	6.30m	5.40-9.00m	9,500	M-B 320/340hp
C7206 TS Balance	£315,050	6.30m	5.40-9.00m	9,500	M-B 320/340hp
C7206 TS Top-Line Extra Power	£311,389	6.30m	5.40-9.00m	9,500	M-B 381hp
C7206 TS Balance Extra Power	£331,124	6.30m	5.40-9.00m	9,500	M-B 381hp
C9000-series Threshing: 1.27m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and five walkers – 7.36sq m. Sieve area: 5.28sq m.					
C9305 TS	£ tbc	6.30m	4.80-7.20m	10,500	M-B 354hp
C9305 TS 4wd	£ tbc	6.30m	4.80-7.20m	10,500	M-B 354hp
C9305 TS Balance	£ tbc	6.30m	4.80-7.20m	10,500	M-B 354hp
C9305 TS Balance 4wd	£ tbc	6.30m	4.80-7.20m	10,500	M-B 354hp
C9000-series Threshing: 1.52m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and six walkers – 8.8sq m. Sieve area: 6.32sq m.					
C9306 TS	£332,999	7.20m	5.40-9.00m	10,500	M-B 381hp
C9306 TS 4wd	£366,576	7.20m	5.40-9.00m	10,500	M-B 381hp
C9306 TS Balance	£353,538	7.20m	5.40-9.00m	10,500	M-B 381hp
C9306 TS Balance 4wd	£384,168	7.20m	5.40-9.00m	10,500	M-B 381hp
<i>Note: Reduced specification (Farm-Line equivalent) available with Top-Line deduct options. TS - Turbo Separator with concave adjustable out of work for dry, brittle conditions. TSB Balance - automatic 20% lateral, 6% fore-aft self-levelling chassis; TSXB Balance available to special order with rear axle lift for 22% lateral, 28% uphill, 5% downhill self-levelling. Cutting tables: Standard with retracting crop feed tines across full width; Varicrop with 700mm hydraulic fore-aft knife position adjustment. Agrosky auto steering optional on C7000 and C9000 ranges. Optional tracks available for C7000 and C9000 with 716mm and 915mm traction belt widths. Distributor: SDF UK.</i>					
FENDT					NEW IDEAL 10
E-series Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers – 6.72sq m. Sieve area: 4.67sq m.					
5185E	£149,290	4.20m FF	4.80-6.00m FF	5,200	Agco 176hp
5225E	£170,890	4.80m FF	6.00-7.60m FF or 5.50m PF	6,500	Agco 218hp
L-series Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers – 7.62sq m. Sieve area: 4.67sq m.					
5225L	£195,700	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
5225L	£195,700	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
L-series Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers – 7.62sq m. Sieve area: 4.67sq m.					
5225L MCS	£202,800	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
5225L MCS ParaLevel	£240,580	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
L-series Threshing: 1.60m x 600mm cylinder. Separation: Beater and six walkers – 8.30sq m. Sieve area: 5.58sq m.					
6275L	£215,350	6.00m FF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 276/306hp
L-series Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers – 9.00sq m. Sieve area: 5.58sq m.					
6275L MCS	£222,460	6.00m FF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 276/306hp
6275L MCS ParaLevel 4wd	£260,230	6.00m FF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 276/306hp
C-series Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers – 6.72sq m. Sieve area: 4.67sq m.					
5275C	£234,090	6.00m FF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 276/306hp
5275C ParaLevel 2wd	£248,960	6.00m FF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 276/306hp
5275C ParaLevel 4wd	£263,790	6.00m FF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 276/306hp
C-series Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers – 9.00sq m. Sieve area: 5.58sq m.					
6335C	£245,080	7.00m FF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 320/360hp

ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
6335C Atrak	£295,750	7.00m FF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 320/360hp
6335C ParaLevel 4wd	£282,530	7.00m FF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 320/360hp
6335C ParaLevel Integrale 4wd	£303,040	6.00m FF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 320/360hp
Ideal 7 Threshing: One 4.83m x 600mm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 4.90sq m.					
Ideal 7	£404,950	9.20m PF/SF	7.70-10.70m PF/SF	12,500 or 17,100	Agco 451hp
Ideal 7 ParaLevel	£419,530	9.20m PF/SF	7.70-10.70m PF/SF	12,500	Agco 451hp
Ideal 7 TrakRide	£445,520	9.20m PF/SF	7.70-10.70m PF/SF	12,500 or 17,100	Agco 451hp
Ideal 8 Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 4.90sq m.					
Ideal 8	£446,580	10.70m PF/SF	9.20-12.20m PF/SF	12,500 or 17,100	MAN 538hp
Ideal 8 ParaLevel	£460,650	10.70m PF/SF	9.20-12.20m PF/SF	12,500	MAN 538hp
Ideal 8 TrakRide	£491,630	10.70m PF/SF	9.20-12.20m PF/SF	12,500 or 17,100	MAN 538hp
Ideal 9 Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 4.06sq m. Sieve area: 5.40sq m.					
Ideal 9	£504,510	12.20m PF/SF	9.20-10.70m PF/SF	17,100 or 12,500	MAN 647hp
Ideal 9 ParaLevel	£514,270	12.20m PF/SF	9.20-10.70m PF/SF	12,500	MAN 647hp
Ideal 9 TrakRide	£549,560	12.20m PF/SF	9.20-10.70m PF/SF	17,100 or 12,500	MAN 647hp
Ideal 10 Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 4.54sq m. Sieve area: 5.40sq m.					
Ideal 10 TrakRide	£600,910	12.20m PF/SF	9.20-10.70m PF/SF	17,100 or 12,500	MAN 790hp
<p><i>Note: AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. IdealBalance shaped grain pan on Ideal models provides up to 15% side slope compensation. Boost power on L-series models available when unloading. Cutting tables: FF - Free Flow; PF - Power Flow with 610mm auger and PF/SF - Power Flow with 760mm Super Flow auger have extended cutterbar position with short conveyor belt feed to auger. Ground speed adjusting feed-rate control optional on Ideal models with 12.2m Super Flow table. Yield meter/moisture sensor - E- and L-series not available; C-series optional; Ideal models standard with mapping optional. AutoGuide auto-steering option £6,210. TrakRide - 660mm traction belt on rubber block suspension undercarriage; TrakRide - 610mm, 760mm and 910mm traction belts with hydraulic suspension. Optional four-wheel drive: L-series and C-series £14,830; Ideal AllDrive £18,340. Joystick steering optional on all Ideal TrakRide models. Distributor: Fendt UK & Ireland.</i></p>					
JOHN DEERE			NEW X9-SERIES		
W300/W400/W500/W600-series			DISCONTINUED		
T500-series Threshing: 1.4m x 660mm cylinder. Separation: 400mm diameter, 140mm stripper roller, 500mm overshot beater, 800mm separator drum, 400mm beater (3.30sq m) and five walkers - 4.80sq m. Sieve area: 5.20sq m.					
T550	£291,271	6.70m 600R	6.10-7.60m	8,000 or 10,000	Deere 271/300hp
T550 HillMaster	£309,095	6.70m 600R	6.10-7.60m	8,000 or 10,000	Deere 271/300hp
T560	£348,196	7.60m 700X	6.70-7.60m	10,000	Deere 334/382hp
T560 ProDrive	£358,741	7.60m 700X	6.70-7.60m	10,000	Deere 334/382hp
T560 ProDrive HillMaster	£364,365	7.60m 700X	6.70-9.15m	10,000	Deere 334/382hp
T560 ProDrive Tracks	£425,754	7.60m 700X	6.70-9.15m	10,000	Deere 334/382hp
T600-series Threshing: 1.67m x 660mm cylinder. Separation: 400mm diameter, 140mm stripper roller, 500mm overshot beater, 800mm separator drum, 400mm beater (4.0sq m) and six walkers - 5.80sq m. Sieve area: 6.30sq m.					
T660	£348,603	9.15m 700X	6.70-10.70m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive	£359,148	9.15m 700X	6.70-10.70m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive HillMaster	£366,976	9.15m 700X	6.70-10.70m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive Tracks	£430,986	9.15m 700X	6.70-10.70m	9,000 or 11,000	Deere 334/382hp
T670	£384,721	9.15m 700X	6.70-10.70m	11,000	Deere 392/449hp
T670 ProDrive	£395,266	9.15m 700X	6.70-10.70m	11,000	Deere 392/449hp
T670 ProDrive HillMaster	£402,766	9.15m 700X	6.70-10.70m	11,000	Deere 392/449hp
T670 ProDrive Tracks	£462,819	9.15m 700X	6.70-10.70m	11,000	Deere 392/449hp
S700-series Threshing: feed drum and 762mm x 3.12m rotor. Separation: rotor diameter increased to 838mm - 3.0 or 3.09sq m. Sieve area: 5.20sq m.					
S770	£408,423	9.15m 700X	7.60m	10,600	Deere 391/449hp
S770 ProDrive	£418,968	9.15m 700X	7.60m	10,600	Deere 391/449hp
S770 ProDrive Tracks	£483,709	9.15m 700X	7.60m	10,600	Deere 391/449hp
S770 ProDrive HillMaster	£442,530	9.15m 700X	7.60m	10,600	Deere 391/449hp
S780 ProDrive	£473,908	9.15m 700X	7.60-10.70m	14,100	Deere 473/540hp
S780 ProDrive Tracks	£538,649	9.15m 700X	7.60-10.70m	14,100	Deere 473/540hp
S780 ProDrive HillMaster	£484,453	9.15m 700X	n/a	10,600	Deere 473/540hp
S785 ProDrive	£495,969	10.70m 700X	7.60-12.20m	14,100	Deere 500/570hp
S785 ProDrive Tracks	£560,710	10.70m 700X	7.60-12.20m	14,100	Deere 500/570hp
S785 ProDrive HillMaster	£494,866	9.15m 700X	n/a	10,600	Deere 500/570hp
S790 ProDrive	£512,260	10.70m 700X	7.60-12.20m	14,100	Deere 543/617hp
S790 ProDrive Tracks	£577,001	10.70m 700X	7.60-12.20m	14,100	Deere 543/617hp

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
S790 ProDrive HillMaster	£511,157	9.15m 700X	n/a	10,600	Deere 543/617hp
X9-series Threshing: feed drum and two 610mm x 3.51m rotors. Separation: two 610mm x 3.51m rotors - 3.44sq m. Sieve area: 7.0sq m.					
X9 1000 ProDrive XL	£756,793	12.20m HDX	13.70m HDR	14,800	Deere 586hp/639hp
X9 1000 ProDrive XL Tracks	£811,653	12.20m HDX	13.70m HDR	14,800	Deere 586hp/639hp
X9 1100 ProDrive XL	£806,668	13.70m HDX	15.20m HDR	16,200	Deere 647hp/700hp
X9 1100 ProDrive XL Tracks	£861,528	13.70m HDX	15.20m HDR	16,200	Deere 647hp/700hp

Note: S700-series prices include five years' JDLink Access subscription; X9 models two years.. Selected models available with "i" precision farming specifications, including JDLink, AutoTrac GPS auto steering and HarvestDoc crop recording. ProDrive - 40kph IVT hydrostatic transmission with auto two-speed gearbox and diff lock; ProDrive XL - 40kph twin pump IVT hydrostatic drive. HillMaster - automatic 15% chassis levelling plus 7% sieve compensation. Front end options - 600R conventional; 600PF and 700PF (Premium Flow) with belt feed between forward-positioned knife and auger; 700X with 710mm of hydraulic fore-aft knife positioning; 700D (not for HillMaster models) belt centre-feeding table; 700FD (not for HillMaster models) belt centre-feed table with 190mm knife flexibility for contoured surfaces; HDR and HDX three-section hinged draper tables with 10deg wing movement and 1,000mm (HDR) and 1,200mm (HDX) patterned belts. Tracks - 610mm or 762mm traction belt on undercarriage with hydro-pneumatic suspension. Optional four-wheel drive: £19,641 for all models with wheels or tracks. Distributor: John Deere.

MASSEY FERGUSON

MF 7300 Activa Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 6.72sq m. Sieve area: 4.67sq m.					
7340	£149,290	4.80m FF	4.20-6.00m FF	5,200	Agco 176hp
7344	£170,890	4.80m FF	6.00-7.60m FF or 5.50m PF	6,500	Agco 218hp
MF 7300 Activa Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 5.73sq m. Sieve area: 4.67sq m.					
7345 S	£195,700	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
MF 7300 Activa Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.					
7345 S MCS	£202,800	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
7345 S MCS ParaLevel 2wd	£240,580	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
7345 S MCS ParaLevel 4wd	£255,410	5.40m FF	4.80-7.60m FF or 6.20m PF	8,600	Agco 243hp
MF 7300 Activa Threshing: 1.60m x 600mm cylinder. Separation: Beater and six walkers - 8.30sq m. Sieve area: 5.58sq m.					
7347 S	£215,350	5.80m FF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 243hp
MF 7300 Activa Threshing: 1.60m x 60cm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9.00sq m. Sieve area: 5.58sq m.					
7347 S MCS	£222,460	6.00m PF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 276hp
7347 S MCS ParaLevel 4wd	£237,290	6.00m PF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 276/306hp
MF 7300 Beta Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 6.72sq m. Sieve area: 4.67sq m.					
7360	£246,320	6.00m PF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 276/306hp
7360 ParaLevel 2wd	£276,020	6.00m PF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 276/306hp
7360 ParaLevel 4wd	£290,850	6.00m PF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 276/306hp
7360 ParaLevel Integrale	£296,520	6.00m PF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 276/306hp
MF 7300 Beta Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9.00sq m. Sieve area: 5.58sq m.					
7370	£264,240	6.70m PF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 320/360hp
7370 Atrak	£287,650	6.70m PF	4.80-7.60m FF or 5.40-6.80m PF	9,000	Agco 320/360hp
7370 ParaLevel 4wd	£292,390	6.70m PF	4.80-7.60m FF or 5.40-6.80m PF	8,600	Agco 320/360hp
7370 ParaLevel Integrale 4wd	£312,900	6.70m PF	4.80-7.60m FF or 5.40-6.20m PF	8,600	Agco 320/360hp
Ideal 7 Threshing: One 4.83m x 600mm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 4.90sq m.					
Ideal 7	£404,950	9.20m PF/SF	7.70-10.70m PF/SF	12,500 or 17,100	Agco 392/451hp



Smarter packaging and power-efficiency solutions help John Deere X9 combines achieve high outputs

JOHN DEERE

The CH7.70 'crossover harvesting' combine is the first from NH to marry conventional threshing with rotary separation



NEW HOLLAND

ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
Ideal 7 ParaLevel	£419,530	9.20m PF/SF	7.70-10.70m PF/SF	12,500	Agco 392/451hp
Ideal 7 TrakRide	£445,520	9.20m PF/SF	7.70-10.70m PF/SF	12,500 or 17,100	Agco 392/451hp
Ideal 8 Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing – 3.58sq m. Sieve area: 4.90sq m.					
Ideal 8	£447,670	10.70m PF/SF	9.20-12.20m PF/SF	12,500 or 17,100	MAN 470/538hp
Ideal 8 ParaLevel	£462,100	10.70m PF/SF	9.20-12.20m PF/SF	12,500	MAN 470/538hp
Ideal 8 TrakRide	£492,720	10.70m PF/SF	9.20-12.20m PF/SF	12,500 or 17,100	MAN 470/538hp
Ideal 9 Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing – 4.06sq m. Sieve area: 5.40sq m.					
Ideal 9	£504,510	12.20m PF/SF	9.20-10.70m PF/SF	17,100 or 12,500	MAN 564/647hp
Ideal 9 ParaLevel	£514,270	12.20m PF/SF	9.20-10.70m PF/SF	12,500	MAN 564/647hp
Ideal 9 TrakRide	£549,560	12.20m PF/SF	9.20-10.70m PF/SF	17,100	MAN 564/647hp
<i>Note: ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. IdealBalance shaped grain pan on Ideal models provides up to 15% side slope compensation. Boost power on Beta models available when unloading. Cutting tables: FF – Free Flow; PF – Power Flow with 610mm auger and PF/SF – Power Flow with 760mm Super Flow auger have extended cutterbar position with short conveyor belt behind. Ground speed adjusting feedrate control optional on Ideal models with 12.2m Super Flow table. Yield meter/moisture sensor – MF7340 and MF 7344 not available; MF7345 S and MF7347 S optional; all Beta models optional; Ideal models standard with mapping optional. AutoGuide auto steering optional for Beta and Ideal models £1,620. Atrak – 660mm traction belt on rubber block suspension undercarriage; TrakRide – 610mm, 760mm and 910mm traction belts with hydraulic suspension. Four-wheel drive: Activa and Beta £13,980; Ideal £17,730. Distributor: Massey Ferguson UK & Ireland.</i>					
NEW HOLLAND				NEW CH 7.70	
TC 4 Threshing: 1.04m x 600mm cylinder. Separation: Beater, 600mm peg drum and four walkers – 4.00sq m. Sieve area: 3.27sq m.					
TC 4.90	£174,445	3.90m HCH	4.50m	5,000	FPT 175hp
TC 5 Threshing: 1.3m x 600mm cylinder. Separation: Beater, 600mm peg drum and five walkers – 5.00sq m. Sieve area: 4.13sq m.					
TC 5.70 SmartSieve	£187,349	5.49m HCH	4.88m	5,200	FPT 175hp
TC 5.90 SmartSieve	£210,252	5.49m HCH	4.88m	6,400	FPT 258hp
CX 5 Threshing: 1.3m x 600mm cylinder. Separation: 390mm beater, 590mm peg drum, straw flow beater and five walkers – 7.37sq m. Sieve area: 4.32sq m.					
CX 5.80	£235,423	6.10m HCH	5.18-6.70m	8,300	FPT 258hp
CX 5.90	£250,582	6.70m HCH	6.10m	8,300	FPT 313hp
CX 5.90 Laterale	£266,329	6.70m HCH	6.10m	8,300	FPT 313hp
CX 6 Threshing: 1.56m x 600mm cylinder. Separation: 390mm beater, 590mm peg drum, straw flow beater and six walkers – 8.84sq m. Sieve area: 5.21sq m.					
CX 6.80	£265,141	6.10m HCH	7.32m	9,300	FPT 313hp
CX 6.90	£283,438	7.62m HCH	6.10m	9,300	FPT 340hp
CX 6.90 Laterale	£301,050	7.62m HCH	6.10m	9,300	FPT 340hp
CH 7 Threshing: 1.56m x 600mm cylinder. Separation: 390mm beater, 395mm four-paddle beater and two 542mm x 3.45m rotors – 2.90sq m. Sieve area: 5.21sq m.					
CH 7.70	£279,088	7.62m HCH	6.10m	9,300	FPT 374hp
CX 7 Threshing: 1.3m x 75cm cylinder. Separation: 610mm beater, 750mm peg drum (2.11sq m) and five walkers – 5.56sq m. Sieve area: 5.40sq m.					
CX 7.80 SL	£295,562	6.10m HCH	5.49-7.62m	9,000	FPT 340hp
CX 7.90 SL	£315,832	6.70m HCH	5.49-7.62m	10,000	FPT 374hp
CX 7.90 SL SmartTrax	£353,118	6.70m HCH	5.49-7.62m	10,000	FPT 374hp
CX 8 Threshing: 1.56m x 75cm cylinder. Separation: 610mm beater, 750mm-diameter peg drum (2.54sq m) and six walkers – 6.68sq m. Sieve area: 6.50sq m.					
CX 8.70 SL	£328,445	7.62m HCH	6.10m	11,500	FPT 374hp
CX 8.80 SL	£355,623	7.62m HCH	9.15m	11,500	FPT 415hp
CX 8.80 SL SmartTrax	£392,854	7.62m HCH	9.15m	11,500	FPT 415hp
CX 8.90 SL	£359,658	9.15m HCH	7.32m	12,500	FPT 415hp
CX 8.90 SL SmartTrax	£396,322	9.15m HCH	7.32m	12,500	FPT 415hp
CR Threshing: 450mm feed roller and two 430mm x 2.64m variable-speed rotors. Separation: threshing rotors and 1.3m x 400mm beater – 2.43sq m. Sieve area: 5.40sq m.					
CR 7.80 Revelation	£351,755	7.62m HCH	9.15m	9,500	FPT 415hp
CR 7.90 Revelation	£373,642	7.62m HCH	9.15m	11,500	FPT 460hp
CR 8.80 Revelation	£407,491	9.15m HCH	7.62m	12,500	FPT 517hp
CR 8.80 Revelation SmartTrax	£450,409	9.15m HCH	7.62m	12,500	FPT 517hp
CR Threshing: 450mm feed roller and two 560mm x 2.64m variable-speed rotors. Separation: threshing rotors and 1.56m x 400mm beater – 3.06sq m. Sieve area: 6.50sq m.					
CR 8.90 Revelation	£438,421	9.15m HCH	10.70m	12,500	FPT 544hp
CR 8.90 Revelation SmartTrax	£477,680	9.15m HCH	10.70m	12,500	FPT 544hp
CR 9.90 Revelation 12,500	£469,164	10.70m HCH	12.50m	12,500	FPT 544hp
CR 9.90 Revelation SmartTrax	£512,540	10.70m HCH	12.50m	12,500	FPT 544hp
CR 9.90 Revelation SmartTrax	£555,864	10.70m HCH	12.50m	14,500	FPT 544hp
CR10.90 Revelation SmartTrax Terraglide	£618,582	12.50m HCH	10.70m	14,500	FPT 700hp

Note: SmartSieve – dynamic 25% slope compensation; Laterale – 18% lateral self-levelling chassis plus SmartSieve dynamic slope compensation; SL – automatic 17% self-levelling cleaning shoe; CX 7/8 and CR models have OptiClean self-levelling cleaning shoe. VariFeed table with 575mm extending knife optional on all models. OptiSpeed variable-speed straw walkers standard on CX combines. SmartSteer scanning laser auto steering optional for £3,770 on all CX and CR models. IntelliSteer GPS auto steering optional for £9,021 on CX7/8 and CR models. SmartTrax traction belts 61cm and 76cm; SmartTrax with Terraglide suspension 61cm, 72cm and 86cm. Optional four-wheel drive: CX and CR £15,139. Distributor: New Holland Agriculture.