

# ULTIMATE GUIDE COMBINES AND BALERS

## All the latest combine updates and full specs

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Maximum harvesting/unloading power
<b>CASE IH</b>					
<b>Axial-Flow 150-series</b> Threshing: one 760mm x 2.79m three-speed variator-drive rotor. Separation: as for threshing - 2.8sq m. Sieve area: 5.52sq m.					
6150 X-Flow	£340,852	6.7m 3050	5.48-6.1m	10,570	FPT 400hp
7150 X-Flow	£397,663*	8.5m 3050	6.09-9.14m	10,570	FPT 453hp
<b>Axial-Flow 250-series</b> Threshing: one 760mm x 2.62m three-range hydro-drive rotor. Separation: as for threshing - 2.98sq m. Sieve area: 6.5sq m.					
7250	£548,580*	9.14m 3050	8.5-10.7m	11,100	FPT 498hp
7250 X-Tra	£579,503*	9.14m 3050	8.5-10.7m	11,100	FPT 498hp
7250 Accutrac	£611,212*	9.14m 3050	8.5-10.7m	11,100	FPT 498hp
7250 X-Tra Accutrac	£642,135*	9.14m 3050	8.5-10.7m	11,100	FPT 498hp
8250 X-Tra	£643,925*	10.7m 3050	9.14-12.5m	14,440	FPT 571hp
8250 X-Tra Accutrac	£706,684*	10.7m 3050	9.14-12.6m	14,440	FPT 571hp
9250 X-Tra	£712,034*	12.5m 3050	9.14-10.7m	14,440	FPT 634hp
9250 X-Tra Accutrac	£774,793*	12.5m 3050	9.14-10.7m	14,440	FPT 634hp
<i>Note: *Prices for Axial-Flow 7150 X-Flow and all 250-series combines include a cutting table trailer for distribution transport ease and safety: 7.62m £19,616; 9.14m £20,981; 10.7m £22,680; 12.5m £26,286. X-Tra models equipped with Redekop MAV straw chopper and chaff distributor in addition to standard straw chopper. "ST" (small tube) threshing and separation rotor standard on all models. Cutting tables: 3050-series - 570mm fore-aft knife adjustment. Slope compensation: Axial-Flow 150-series - X-Flow cleaning system for hillside compensation up to 12%; 250-series - self-levelling shaker shoe assembly for 12% slope compensation. Management: AFS Harvest Command auto settings optimisation and automatic feedrate control option. Guidance: 150-series - AFS AccuGuide satellite auto steering option; 250-series - AFS AccuGuide satellite autosteering standard. Traction - Accutrac traction belt widths 61cm, 72cm and 86cm. Four-wheel drive option £22,274. Distributor: Case IH Agriculture.</i>					
<b>CLAAS</b>			<b>*NEW MODELS; **REVAMPED SERIES</b>		
<b>Tucano 320</b>			<b>DISCONTINUED</b>		
<b>Trion 500-series</b> Threshing: 1.42m x 600mm cylinder. Separation: 450mm acceleration/separation drum ahead of threshing cylinder, beater drum and five walkers with overhead tined agitator drum - 6.25sq m. Sieve area: 5.1sq m.					
520	£255,280	6.2m V	5-6.8m V	8,000	Cummins 258hp
530	£267,340	6.8m V	5-6.2m V	9,000 or 10,500	Cummins 306hp
530 Montana	£273,480	6.8m V	5-6.2m V	9,000 or 10,500	Cummins 306hp
530 Terra-Trac	£323,710	6.8m V	5-6.2m V	9,000 or 10,500	Cummins 306hp
540*	£281,380	6.8m V	5-6.2m V	9,000 or 10,500	Cummins 354hp
540 Terra-Trac*	£330,380	6.8m V	5-6.2m V	9,000 or 10,500	Cummins 354hp
<b>Trion 600-series</b> Threshing: 1.70m x 600mm cylinder. Separation: 450mm acceleration/separation drum ahead of threshing cylinder, beater drum and six walkers with overhead tined agitator drum - 7.48sq m. Sieve area: 5.8sq m.					
640	£303,950	7.7m V	6.2-9.3m V/C/CF	9,000	Cummins 306hp
650	£318,820	7.7m V	6.2-9.3m V/C/CF	10,500	Cummins 354hp
650 Montana	£337,680	7.7m V	6.2-9.3m V/7.7m C or CF	10,500	Cummins 354hp
650 Terra-Trac	£360,550	7.7m V	6.2-9.3m V/C/CF	10,500	Cummins 354hp
660	£344,650	7.7m V	6.2-9.3m V/C/CF	10,500	Cummins 408hp
660 Montana	£357,080	7.7m V	6.2-9.3m V/7.7m C or CF	11,000	Cummins 408hp
660 Terra-Trac	£381,400	7.7m V	6.2-9.3m V/C/CF	10,500	Cummins 408hp
<b>Trion 700-series</b> Threshing: 1.42m x 600mm cylinder. Separation: 450mm acceleration/separation drum ahead of threshing cylinder, beater drum and one 57cm x 4.2m variable-speed rotor - 2.58sq m (total including APS 4.02sq m). Sieve area: 5.1sq m.					
720	£310,180	7.7m V	6.2-9.3m V/C/CF	10,500 or 12,000	Cummins 367hp
720 Montana	£341,200	7.7m V	6.2-9.3m V/7.7m C or CF	10,500	Cummins 367hp
720 Terra-Trac	£360,600	7.7m V	6.2-9.3m V/C/CF	10,500 or 12,000	Cummins 367hp
730	£339,300	9.3m V	6.8-10.8m V/C/CF	11,000 or 12,000	Cummins 367hp
730 Montana	£359,360	9.3m V	6.8-10.8m V/7.7m C or CF	11,000	Cummins 408hp
730 Terra-Trac	£388,380	9.3m V	6.8-10.8m V/C/CF	11,000 or 12,000	Cummins 408hp
<b>Trion 700-series</b> Threshing: 1.42m x 600mm cylinder. Separation: 450mm acceleration/separation drum ahead of threshing cylinder, beater drum and two 44cm x 4.2m variable-speed rotor - 3sq m (total including APS 4.44sq m). Sieve area: 5.1sq m.					
750	£410,400	9.3m V	6.8-10.8m V/C/CF	12,000	Cummins 435hp
750 Montana	£436,950	9.3m V	6.8-9.3m V/7.7m C or CF	11,000	Cummins 435hp
750 Terra-Trac	£465,220	9.3m V	6.8-10.8m V/C/CF	12,000	Cummins 435hp
<b>Lexion 5000-series**</b> Threshing: 1.42m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, 600mm peg drum, beater and five walkers - 5.4sq m. Sieve area: 5.1sq m.					
5300	£315,690	7.7m V	5.4-7.7m V/C/CF	10,000 or 9,000	M-B 313hp
5400	£325,410	7.7m V	6.2-7.7m V/C/CF	10,000	M-B 354hp
5500 Montana*	£366,780	7.7m V	6.2-7.7m V	10,000	M-B 408hp
5500 Terra Trac	£399,040	7.7m V	6.2-9.3m V/C/CF	11,000 or 10,000	M-B 408hp
<b>Lexion 6000-series**</b> Threshing: 1.70m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, 600mm peg drum, beater and six walkers - 6.37sq m. Sieve area: 6.2sq m.					



Self-levelling Montana combines are back in the Lexion range

PETER HILL, FENDT



New entry-level Fendt Corus combines have a choice of separation systems

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
6600	£359,130	7.7m V	6.2-7.7m V/C/CF	10,000 or 9,000	M-B 354hp
6700	£389,780	9.3m V	6.2-7.7m V/C/CF	11,000 or 10,000	M-B 408hp
6700 Terra Trac	£443,770	9.3m V	6.2-7.7m V/C/CF	11,000 or 10,000	M-B 408hp
6800	£405,160	9.3m V	6.8-10.8m V/C/CF	12,500 or 11,000	M-B 462hp
6800 Terra Trac	£466,190	9.3m V	6.8-10.8m V/C/CF	12,500 or 11,000	M-B 462hp
6900	£420,520	9.3m V	6.8-10.8m V/C/CF	13,500 or 12,000	MAN 507hp
6900 Terra Trac	£484,320	9.3m V	6.8-10.8m V/C/CF	13,500 or 12,000	MAN 507hp
<b>Lexion 7000-series**</b> Threshing: 1.42m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, feed drum and two 44.5cm x 4.2m variable-speed rotors - 3sq m (total including APS 4.69sq m). Sieve area: 5.1sq m.					
7400	£402,640	7.7m V	6.8-10.8m V/C/CF	10,000 or 11000	M-B 408hp
7500	£471,000	9.3m V	6.8-10.8m V/C/CF	11,000 or 12,500	M-B 462hp
7500 Terra Trac	£519,850	9.3m V	6.8-10.8m V/C/CF	11,000 or 12,500	M-B 462hp
7600	£530,140	9.3m V	7.7-10.8m V/C/CF	11,000 or 12,500	MAN 507hp
7600 Terra Trac	£594,770	10.8m V	7.7-10.8m V/C/CF	12,500	MAN 507hp
7700	£559,400	10.8m V	7.7-12.3m V/C/CF	13,500	MAN 549hp
7700 Montana*	£559,850	9.3m V	7.7-9.3m V/C/CF	11,000	MAN 549hp
7700 Terra Trac	£615,420	12.3m V	9.3-12.3m V/C/CF	13,500	MAN 549hp
<b>Lexion 8000-series**</b> Threshing: 1.70m x 755mm cylinder. Separation: 600mm acceleration/separation drum ahead of threshing cylinder, feed drum and two 44.5cm x 4.2m variable-speed rotors - 3.6sq m (total including APS 5.62sq m). Sieve area: 6.2sq m.					
8600*	£581,050	12.3m V	10.8m V/C/CF	12,500	MAN 549hp
8600 Terra Trac*	£626,050	12.3m V	10.8m V/C/CF	13,500	MAN 549hp
8700 Terra Trac	£662,440	12.3m V	10.8m V/C/CF	13,500 or 15,000	M-B 625hp
8800 Terra Trac	£729,910	13.8m V	10.8-13.8m V/C/CF	15,000 or 18,000	MAN 700hp
8900 Terra Trac	£756,790	13.8m V	10.8-13.8m V/C/CF	15,000 or 18,000	MAN 790hp
<i>Note: Dynamic Power on all Trion and Lexion models automatically regulates engine output according to load for field and road. Maximum speed - Trion 30kph, Lexion 40kph. Cutting tables: V - Auto Contour Vario (with 700mm hydraulic fore-aft knife adjustment); options - Cerio 5.60-9.30m with 200mm manual fore-aft knife adjustment, C - Convio 7.7-13.8m rigid draper, CF - Convio Flex 7.7-13.8m draper with flexible knife. Side knives available on Vario, Convio and Convio Flex headers. Slope compensation: Trion 500/600 - optional 3D dynamic top sieve for up to 20% slope compensation; Trion 700 - optional 4D dynamic sieve action and rotor cage flap control for up to 20% slope compensation. Trion Montana - chassis side-to-side levelling up to 18%, fore-aft up to 6%. Lexion 5000/6000 - optional 3D dynamic top sieve for up to 20% slope compensation. Lexion 7000/8000 - 3D dynamic sieve action and 4D rotor cage flap control for up to 20% slope compensation standard on 7600, 7700, 8800 and 8900, optional on other rotary separation models. Lexion Montana - chassis side-to-side levelling up to 18%, fore-aft up to 6%. Management: Trion and Lexion - Cemos Dialog settings advice and Cemos Automatic settings optimisation optional on all models; Cemos Auto Header Vario table depth and reel position adjustment optional on all models; requires Field Scanner, Cruise Pilot automatic forward speed control optional on all models. Guidance: Trion - optional Laser Pilot (header-mounted) for Montana and Field Pilot (cab-mounted) laser-scanning, GPS Pilot satellite and Auto Pilot (maize) autosteering systems. Lexion - optional Field Pilot (cab-mounted) laser-scanning, GPS Pilot satellite and Auto Pilot (maize) auto steering systems. Traction: Terra Trac rubber track suspension undercarriage with 635mm, 735mm or 890mm traction belts. Four-wheel-drive option - all models £19,725. Distributor: Claas UK.</i>					
<b>DEUTZ-FAHR</b>					
<b>C6000-series</b> Threshing: 1.27m x 600mm cylinder. Separation: Beater and five walkers - 6.23sq m. Sieve area: 4.22sq m.					
C6205 Farm-Line	£202,435	4.8m STD	3.6-5.4m STD or 5-6.5m V	7,000	M-B 250hp
C6205 Top-Line	£211,135	4.8m STD	3.6-5.4m STD or 5-6.5m V	7,000	M-B 250hp
<b>C6000-series</b> Threshing: 1.27m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and five walkers - 6.36sq m. Sieve area: 4.22sq m.					
C6205 TS Farm-Line	£211,200	4.8m STD	3.6-5.4m STD or 5-6.5m V	7,000	M-B 250hp
C6205 TS Top-Line	£221,725	4.8m STD	3.6-5.4m STD or 5-6.5m V	7,000	M-B 250hp
<b>C7000-series</b> Threshing: 1.27m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and five walkers - 7.36sq m. Sieve area: 5.28sq m.					
C7205 TS Top-Line	£295,985	6.3m STD	4.8-7.2m STD or 5-7.5m V	8,500	M-B 288/309hp
C7205 TSB Balance	£318,900	6.3m STD	4.8-7.2m STD or 5-7.5m V	8,500	M-B 288/309hp
<b>C7000-series</b> Threshing: 1.52m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and six walkers - 8.8sq m. Sieve area: 6.32sq m.					
C7206 TS Top-Line	£346,395	6.3m STD	5.4-9m STD or 5-7.5m V	9,500	M-B 320/340hp
C7206 TS Balance	£369,325	6.3m STD	5.4-9m STD or 5-7.5m V	9,500	M-B 320/340hp
<b>C9000-series</b> Threshing: 1.52m x 600mm cylinder. Separation: Beater, 59cm-diameter peg drum adjustable out of crop flow and six walkers - 8.8sq m. Sieve area: 6.32sq m.					
C9306 TS	£392,965	7.2m STD	5.4-9m STD or 5.5-7.5m V	10,500	M-B 381hp

# ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank (litres)	Max harvesting/unloading power
C9306 TS 4wd	£431,600	7.2m STD	5.4-9m STD or 5.5-7.5m V	10,500	M-B 381hp
C9306 TS Balance	£416,780	7.2m STD	5.4-9m STD or 5.5-7.5m V	10,500	M-B 381hp
C9306 TS Balance 4wd	£455,425	7.2m STD	5.4-9m STD or 5.5-7.5m V	10,500	M-B 381hp

Note: C7000-series highest power outputs available when unloading on the move. Reduced specification (Farm-Line equivalent) available with Top-Line deduct options. TS - Turbo Separator with concave adjustable out of work for dry, brittle conditions. Cutting tables: STD - Standard fixed-knife table; V - Varicrop 5-7.5m with 700mm hydraulic fore-aft knife adjustment. Slope compensation: TSB Balance - automatic 20% lateral, 6% fore-aft self-levelling chassis; TSXB Balance available to special order with rear axle lift for 22% lateral, 28% uphill, 5% downhill self-levelling. Management: Crop default settings. Guidance: C7000 and C9000 - SDF Guidance satellite autosteering optional. Traction: C7000 and C9000 - optional tracks with 716mm and 915mm traction belts. Distributor: SDF UK.

## FENDT

\*UPDATED MODELS; \*\*ADDITIONAL MODEL

### 5185E/5225E

DISCONTINUED

**Corus 500 Gen 1** Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 6.72sq m. Sieve area: 4.67sq m.

Corus 518*	£157,122	4.2m FF	4.8-7.6m FF or 6.2m PF	5,200	Agco 185hp
Corus 522*	£168,125	4.8m FF	4.2-7.6m FF or 6.2m PF	6,500	Agco 225hp
Corus 526**	£184,214	5.4m FF	4.8-7.6m FF or 6.2m PF	6,500	Agco 260hp

**Corus 500 Gen 1** Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.

Corus 518 MCS*	£167,227	4.2m FF	4.8-7.6m FF or 6.2m PF	5,200	Agco 185hp
Corus 522 MCS*	£178,232	4.8m FF	4.2-7.6m FF or 6.2m PF	6,500	Agco 225hp
Corus 526 MCS**	£194,319	5.4m FF	4.8-7.6m FF or 6.2m PF	6,500	Agco 260hp

**L-series** Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 6.72sq m. Sieve area: 4.67sq m.

5255L	£205,900	5.4m FF	4.8-7.6m FF or 6.2m PF	8,600	Agco 243hp
<b>L-series</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.					
5255L MCS Plus	£213,400	5.4m FF	4.8-7.6m FF or 6.2m PF	8,600	Agco 243hp
5255L MCS Plus ParaLevel	£252,670	5.4m FF	4.8-7.6m FF or 6.2m PF	8,600	Agco 243hp

**L-series** Threshing: 1.60m x 600mm cylinder. Separation: Beater and six walkers - 8.30sq m. Sieve area: 5.58sq m.

6275L	£226,660	6m FF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 276/306hp
<b>L-series</b> Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9sq m. Sieve area: 5.58sq m.					
6275L MCS Plus	£234,160	6m FF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 276/306hp
6275L MCS Plus ParaLevel 4wd	£273,430	6m FF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 276/306hp

**C-series** Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.

5275C MCS Plus	£246,360	6m FF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 276/306hp
5275C MCS Plus ParaLevel 2wd	£261,760	6m FF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 276/306hp
5275C MCS Plus ParaLevel 4wd	£277,090	6m FF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 276/306hp

**C-series** Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9sq m. Sieve area: 5.58sq m.

6335C MCS Plus	£267,780	7m FF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 320/360hp
6335C MCS Plus Atrak	£309,060	7m FF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 320/360hp
6335C MCS Plus ParaLevel 4wd	£296,860	7m FF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 320/360hp
6335C MCS Plus ParaLevel Integrale 4wd	£314,470	6m FF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 320/360hp

**Ideal 7** Threshing: One 4.83m x 600mm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 4.9sq m.

Ideal 7	£434,810	9.2m PF/SF	7.7-10.7m PF/SF	12,500 or 17,100	Agco 392/451hp
Ideal 7 ParaLevel	£450,170	9.2m PF/SF	7.7-10.7m PF/SF	12,500	Agco 392/451hp
Ideal 7 TrakRide	£475,960	9.2m PF/SF	7.7-10.7m PF/SF	12,500 or 17,100	Agco 392/451hp

**Ideal 8** Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 4.90sq m.

Ideal 8	£482,060	10.7m PF/SF	9.2-12.2m PF/SF	12,500 or 17,100	MAN 470/538hp
Ideal 8 ParaLevel	£496,920	10.7m PF/SF	9.2-12.2m PF/SF	12,500	MAN 470/538hp
Ideal 8 TrakRide	£527,790	10.7m PF/SF	9.2-12.2m PF/SF	12,500 or 17,100	MAN 470/538hp

**Ideal 9** Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 4.06sq m. Sieve area: 5.4sq m.

Ideal 9	£540,180	12.2m PF/SF	9.2-10.7m PF/SF	17,100 or 12,500	MAN 564/647hp
Ideal 9 ParaLevel	£550,480	12.2m PF/SF	9.2-10.7m PF/SF	12,500	MAN 564/647hp
Ideal 9 TrakRide	£585,910	12.2m PF/SF	9.2-10.7m PF/SF	17,100 or 12,500	MAN 564/647hp

**Ideal 10** Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 4.54sq m. Sieve area: 5.4sq m.

Ideal 10 TrakRide	£639,410	12.2m PF/SF	9.2-10.7m PF/SF	17,100 or 12,500	MAN 790hp
-------------------	----------	-------------	-----------------	------------------	-----------

Note: Highest power outputs available when unloading. Ideal 8T and 9T - Heavy-duty transmission with larger hydraulic pump and motor optional. L- and C-series MCS Plus models - in addition to the separation drum, these models have a retracting tine Power Feed Roller at the crop elevator. Cutting tables: FF - FreeFlow; PF - PowerFlow with 610mm auger and PF/SF - Power Flow with 760mm Super Flow auger have extended cutterbar position with short conveyor belt feed to auger; optional Geringhoff Flex 9m rigid draper with flexible knife, TruFlex/TruFlex Air 10.7m and 12.2m three-section articulated draper with flexible cutterbar. Slope compensation: L- and C-series - ParaLevel 2wd 15%, 4wd 20% automatic side-to-side chassis levelling; C-series - Integrale hydraulic rear lift compensates for slopes 30% uphill, 10% downhill; Ideal - ParaLevel 14% automatic side-to-side chassis levelling; Ideal 8/9/10 - IdealBalance shaped grain pan compensates up to 15% side slopes. Management: L- and C-series - default crop settings; Ideal - optional Idealharvest iPad app for automatic settings optimisation and automatic ground speed control. Guidance: AutoGuide satellite autosteering option. Traction: TrakRide - 660mm traction belt on rubber block suspension undercarriage; TrakRide - 610mm, 760mm and 910mm traction belts with hydraulic suspension. Optional four-wheel drive: L-series and C-series £15,050; Ideal AllDrive £18,620. Joystick steering optional on all Ideal TrakRide models. Distributor: Fendt UK & Ireland.

## JOHN DEERE

**T500-series** Threshing: 1.4m x 660mm cylinder. Separation: 400mm diameter, 140mm stripper roller, 500mm overshot beater, 800mm separator drum, 400mm beater (3.3sq m) and five walkers - 4.8sq m. Sieve area: 5.2sq m.

T550	£361,696	6.7m 600R	6.1-7.6m	8,000 or 10,000	Deere 271/300hp
T550 HillMaster	£385,463	6.7m 600R	6.1-7.6m	8,000 or 10,000	Deere 271/300hp
T560	£427,389	7.6m 700X	6.7m	10,000	Deere 334/382hp
T560 ProDrive	£439,420	7.6m 700X	6.7m	10,000	Deere 334/382hp
T560 ProDrive HillMaster	£458,477	7.6m 700X	6.7-9.15m	10,000	Deere 334/382hp
T560 ProDrive Tracks	£511,244	7.6m 700X	6.7-9.15m	10,000	Deere 334/382hp

# ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank - litres	Max harvesting / unloading power
<b>T600-series</b> Threshing: 1.67m x 660mm cylinder. Separation: 400mm diameter, 140mm stripper roller, 500mm overshot beater, 800mm separator drum, 400mm beater (4.0sq m) and six walkers - 5.8sq m. Sieve area: 6.3sq m.					
T660	£439,476	9.15m 700X	6.7-10.7m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive	£455,009	9.15m 700X	6.7-10.7m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive HillMaster	£465,607	9.15m 700X	6.7-10.7m	9,000 or 11,000	Deere 334/382hp
T660 ProDrive Tracks	£528,529	9.15m 700X	6.7-10.7m	9,000 or 11,000	Deere 334/382hp
T670	£472,991	9.15m 700X	6.7-10.7m	11,000	Deere 392/449hp
T670 ProDrive	£485,022	9.15m 700X	6.7-10.7m	11,000	Deere 392/449hp
T670 ProDrive HillMaster	£505,846	9.15m 700X	6.7-10.7m	11,000	Deere 392/449hp
T670 ProDrive Tracks	£556,846	9.15m 700X	6.7-10.7m	11,000	Deere 392/449hp
<b>S700-series</b> Threshing: feed drum and one 762mm x 3.12m rotor. Separation: rotor diameter increased to 838mm - 3 or 3.09sq m. Sieve area: 5.2sq m.					
S770	£519,788	9.15m 700D	7.6m	10,600	Deere 391/449hp
S770 ProDrive	£531,819	9.15m 700D	7.6m	10,600	Deere 391/449hp
S770 ProDrive Tracks	£597,786	9.15m 700D	7.6m	10,600	Deere 391/449hp
S770 ProDrive HillMaster	£558,106	9.15m 700X	7.6m	10,600	Deere 391/449hp
S780 ProDrive	£586,661	9.15m 700D	7.6-10.7m	14,100	Deere 473/540hp
S780 ProDrive Tracks	£651,111	9.15m 700D	7.6-10.7m	14,100	Deere 473/540hp
S780 ProDrive HillMaster	£593,004	9.15m 700X	n/a	10,600	Deere 473/540hp
S785 ProDrive	£626,578	10.7m 700D	7.6-12.2m	14,100	Deere 500/570hp
S785 ProDrive Tracks	£691,028	10.7m 700D	7.6-12.2m	14,100	Deere 500/570hp
S785 ProDrive HillMaster	£603,169	9.15m 700X	n/a	10,600	Deere 500/570hp
S790 ProDrive	£643,678	10.7m 700D	7.6-12.2m	14,100	Deere 543/617hp
S790 ProDrive Tracks	£708,128	10.7m 700D	7.6-12.2m	14,100	Deere 543/617hp
S790 ProDrive HillMaster	£620,364	9.15m 700X	n/a	10,600	Deere 543/617hp
<b>X9-series</b> Threshing: feed drum and two 610mm x 3.51m rotors. Separation: two 610mm x 3.51m rotors - 3.44sq m. Sieve area: 7sq m.					
X9 1000 ProDrive XL	£937,233	12.2m HDX	13.7m HDR	14,800	Deere 586/639hp
X9 1000 ProDrive XL Tracks	£1,005,085	12.2m HDX	13.7m HDR	14,800	Deere 586/639hp
X9 1100 ProDrive XL	£1,003,871	13.7m HDX	15.2m HDR	16,200	Deere 647/700hp
X9 1100 ProDrive XL Tracks	£1,071,723	13.7m HDX	15.2m HDR	16,200	Deere 647/700hp
<i>Note: Highest power outputs available when unloading. S700-series prices include five years' JDLink Access subscription; X9 prices include two years' JDLink Access subscription. Selected models available with "i" precision farming specifications, including JDLink, AutoTrac GPS autosteering and HarvestDoc crop recording. T-series and S-series - HarvestLab 3000 option for wheat, barley, oilseed constituent measurement and mapping. ProDrive - 40kph IVT hydrostatic transmission with auto two-speed gearbox and diff lock. ProDrive XL - 40kph twin-pump IVT hydrostatic drive. Slope compensation: HillMaster - automatic 15% chassis levelling plus 7% sieve compensation. Cutting tables: 600R 4.9-10.7m conventional; 600PF and 700PF (Premium Flow) 5.15-12.2m with belt feed between forward-positioned knife and auger; 700X 6.7-12.2m with 710mm of hydraulic fore-aft knife positioning; 700D 7.6-12.2m rigid draper (not available for HillMaster models); HDX 10.7-13.7m three-section hinged draper with 10deg wing movement and 1,200mm patterned belts; RDF HydraFlex 9.15-13.7m rigid draper with 190mm vertical knife flexibility (not available for HillMaster models); HDR 10.7-15.2m hinged draper with 1,000mm "grain saver" patterned belts and 10deg wing movement; BP15 4.55m belt pick-up for swathed small grain and oilseed crops. Guidance: AutoTrac satellite system optional. Management: Combine Advisor settings advice and automatic optimisation system optional. Traction: Tracks - 610mm or 762mm traction belt on undercarriage with hydro-pneumatic suspension. Optional four-wheel drive: £23,080. Distributor: John Deere.</i>					
<b>MASSEY FERGUSON</b>			<b>*REVISED MODELS; **ADDITIONAL MODEL</b>		
7340 Activa / 7344 Activa					<b>DISCONTINUED</b>
<b>MF 7300 Activa</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 6.72sq m. Sieve area: 4.67sq m.					
7342*	£181,344	4.8m FF	4.8-6m FF	5,200	Agco 185hp
7343*	£192,384	5.4m FF	4.8-7.6m FF or 5.5-6.2m PF	5,200 or 6,500	Agco 226hp
7344**	£208,500	6m PF	4.8-7.6m FF or 5.5-6.2m PF	6,500	Agco 260hp
<b>MF 7300 Activa</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.					
7342 MCS*	£195,003	4.8m FF	4.8-6m FF	5,200	Agco 185hp
7343 MCS*	£208,161	5.4m PF	4.8-7.6m FF or 5.5-6.2m PF	5,200 or 6,500	Agco 226hp
7344 MCS**	£225,965	6m PF	4.8-7.6m FF or 5.5-6.2m PF	6,500	Agco 260hp
<b>MF 7300 S Activa</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater and five walkers - 5.73sq m. Sieve area: 4.67sq m.					
7345 S	£202,938	6m FF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 243hp
<b>MF 7300 S Activa</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 7.62sq m. Sieve area: 4.67sq m.					
7345 S MCS	£240,883	6m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 243hp
7345 S MCS ParaLevel 2wd	£266,094	6m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 243hp
<b>MF 7300 S Activa</b> Threshing: 1.60m x 600mm cylinder. Separation: Beater and six walkers - 8.30sq m. Sieve area: 5.58sq m.					
7347 S	£223,856	6m PF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 260hp
<b>MF 7300 S Activa</b> Threshing: 1.60m x 60cm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9sq m. Sieve area: 5.58sq m.					
7347 S MCS	£264,255	6m PF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 306hp
7347 S MCS ParaLevel 4wd	£289,466	6m PF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 306hp
<b>MF 7300 Beta</b> Threshing: 1.34m x 600mm cylinder. Separation: Beater, 1.31m x 60cm peg drum with retractable concave and five walkers - 6.72sq m. Sieve area: 4.67sq m.					
7360 MCS	£290,292	6m PF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 276/306hp
7360 MCS ParaLevel 2wd	£315,010	6m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 276/306hp
7360 MCS ParaLevel 4wd	£330,375	6m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 276/306hp
7360 MCS ParaLevel Integrale	£343,477	6m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 276/306hp
<b>MF 7300 Beta</b> Threshing: 1.60m x 600mm cylinder. Separation: Beater, 1.56m x 60cm peg drum with retractable concave and six walkers - 9sq m. Sieve area: 5.58sq m.					
7370 MCS	£323,971	6.7m PF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 320/360hp
7370 MCS Atrak	£367,240	6.7m PF	4.8-7.6m FF or 5.5-6.8m PF	9,000	Agco 320/360hp
7370 MCS ParaLevel 4wd	£330,272	6.7m PF	4.8-7.6m FF or 5.5-6.8m PF	8,600	Agco 320/360hp
7370 MCS ParaLevel Integrale 4wd	£363,859	6.7m PF	4.8-7.6m FF or 5.5-6.2m PF	8,600	Agco 320/360hp



# ULTIMATE GUIDE COMBINES AND BALERS

Model	List price with recommended table	Recommended table	Other table sizes available	Grain tank - litres	Max harvesting / unloading power
<b>Ideal 7</b> Threshing: One 4.83m x 600mm rotor. Separation: as for threshing - 2.27sq m. Sieve area: 4.9sq m.					
Ideal 7	£499,572	9.2m PF/SF	7.7-10.7m PF/SF	12,500 or 17,100	Agco 392/451hp
Ideal 7 ParaLevel	£516,764	9.2m PF/SF	7.7-10.7m PF/SF	12,500	Agco 392/451hp
Ideal 7 TrakRide	£544,780	9.2m PF/SF	7.7-10.7m PF/SF	12,500 or 17,100	Agco 392/451hp
<b>Ideal 8</b> Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 3.58sq m. Sieve area: 4.9sq m.					
Ideal 8	£552,371	10.7m PF/SF	9.2-12.2m PF/SF	12,500 or 17,100	MAN 470/538hp
Ideal 8 ParaLevel	£568,977	10.7m PF/SF	9.2-12.2m PF/SF	12,500	MAN 470/538hp
Ideal 8 TrakRide	£600,693	10.7m PF/SF	9.2-12.2m PF/SF	12,500 or 17,100	MAN 470/538hp
<b>Ideal 9</b> Threshing: Two 4.83m x 600mm rotors. Separation: as for threshing - 4.06sq m. Sieve area: 5.4sq m.					
Ideal 9	£613,320	12.2m PF/SF	9.2-10.7m PF/SF	17,100 or 12,500	MAN 564/647hp
Ideal 9 ParaLevel	£614,977	12.2m PF/SF	9.2-10.7m PF/SF	12,500	MAN 564/647hp
Ideal 9 TrakRide	£666,211	12.2m PF/SF	9.2-10.7m PF/SF	17,100	MAN 564/647hp
<i>Note: Highest power outputs available when unloading. Ideal 8T and 9T - Heavy Duty transmission with larger hydraulic pump and motor optional. Activa and Beta - in addition to the separation drum, MCS models have a retracting tine Power Feed Roller at the base of the crop elevator. Cutting tables: FF - Free Flow; PF - Power Flow with 610mm auger and PF/SF - Power Flow with 760mm Super Flow auger have extended cutterbar position with short conveyor belt behind; optional Geringhoff Flex 9m rigid draper with flexible knife, TruFlex/TruFlex Air 10.7m and 12.2m three-section articulated draper with flexible cutterbar. Slope compensation: Activa and Beta - ParaLevel 2wd 15%, 4wd 20% automatic side-to-side chassis levelling; Beta - Integrable hydraulic rear lift compensates for slopes 30% uphill, 10% downhill, Ideal 7/8/9 - ParaLevel 14% automatic side-to-side chassis levelling; Ideal 8/9 - IdealBalance shaped grain pan compensates up to 15% side slopes. Management: Activa and Beta - default crop settings; Ideal - optional Idealharvest iPad app for automatic settings optimisation and automatic ground speed control. Guidance: AutoGuide satellite auto steering option. Traction: Atrak - 660mm traction belt on rubber block suspension undercarriage; TrakRide - 610mm, 760mm and 910mm traction belts with hydraulic suspension. Four-wheel drive: Activa and Beta £13,980; Ideal AllDrive £17,730. Joystick steering optional on all Ideal TrakRide models. Distributor: Massey Ferguson UK &amp; Ireland.</i>					
<b>NEW HOLLAND</b>					
<b>TC 4</b> Threshing: 1.04m x 600mm cylinder. Separation: Beater, 600mm peg drum and four walkers - 4sq m. Sieve area: 3.27sq m.					
TC 4.90	£184,658	3.9m HCH	4.5m	5,000	FPT 175hp
<b>TC 5</b> Threshing: 1.3m x 600mm cylinder. Separation: Beater, 600mm peg drum and five walkers - 5sq m. Sieve area: 4.13sq m.					
TC 5.70 SmartSieve	£200,823	5.49m HCH	4.88m	5,200	FPT 175hp
TC 5.90 SmartSieve	£225,199	5.49m HCH	4.88m	6,400	FPT 258hp
<b>CX 5</b> Threshing: 1.3m x 600mm cylinder. Separation: 390mm beater, 590mm peg drum, straw flow beater and five walkers - 7.37sq m. Sieve area: 4.32sq m.					
CX 5.80	£276,324	6.1m HCH	5.18-6.7m	8,300	FPT 258hp
CX 5.90	£291,176	6.7m HCH	6.1m	8,300	FPT 313hp
CX 5.90 Laterale	£312,740	6.7m HCH	6.1m	8,300	FPT 313hp
<b>CX 6</b> Threshing: 1.56m x 600mm cylinder. Separation: 390mm beater, 590mm peg drum, straw flow beater and six walkers - 8.84sq m. Sieve area: 5.21sq m.					
CX 6.80	£304,455	6.1m HCH	7.32m	9,300	FPT 313hp
CX 6.90	£325,636	7.62m HCH	6.1m	9,300	FPT 340hp
CX 6.90 Laterale	£346,044	7.62m HCH	6.1m	9,300	FPT 340hp
<b>CH 7</b> Threshing: 1.56m x 600mm cylinder. Separation: 390mm beater, 395mm four-paddle beater and two 542mm x 3.45m rotors - 2.9sq m. Sieve area: 5.21sq m.					
CH 7.70	£337,864	7.62m HCH	6.1m	9,300	FPT 374hp
CH 7.70 Laterale	£391,262	7.62m HCH	6.1m	9,300	FPT 374hp
<b>CX 7</b> Threshing: 1.3m x 750mm cylinder. Separation: 610mm beater, 750mm-diameter peg drum (2.11sq m), straw flow beater and five walkers - 5.56sq m. Sieve area: 5.4sq m.					
CX 7.80 SL	£364,277	6.1m HCH	5.49-7.62m	9,000	FPT 340hp
CX 7.90 SL	£363,842	6.7m HCH	5.49-7.62m	10,000	FPT 374hp
CX 7.90 SL SmartTrax	£415,035	6.7m HCH	5.49-7.62m	10,000	FPT 374hp
<b>CX 8</b> Threshing: 1.56m x 750mm cylinder. Separation: 610mm beater, 750mm-diameter peg drum (2.54sq m), straw flow beater and six walkers - 6.68sq m. Sieve area: 6.5sq m.					
CX 8.70 SL	£378,015	7.62m HCH	6.1m	11,500	FPT 374hp
CX 8.80 SL	£409,280	7.62m HCH	9.15m	11,500	FPT 415hp
CX 8.80 SL SmartTrax	£450,530	7.62m HCH	9.15m	11,500	FPT 415hp
CX 8.90 SL	£413,826	9.15m HCH	7.32m	12,500	FPT 415hp
CX 8.90 SL SmartTrax	£456,590	9.15m HCH	7.32m	12,500	FPT 415hp
<b>CR</b> Threshing: 450mm feed roller and two 430mm x 2.64m variable-speed rotors. Separation: threshing rotors and 1.3m x 400mm beater - 2.43sq m. Sieve area: 5.4sq m.					
CR 7.80 Revelation	£416,083	7.62m HCH	9.15m	9,500	FPT 415hp
CR 7.90 Revelation	£455,377	7.62m HCH	9.15m	11,500	FPT 460hp
CR 8.80 Revelation	£494,966	9.15m HCH	7.62m	12,500	FPT 517hp
CR 8.80 Revelation SmartTrax	£545,040	9.15m HCH	7.62m	12,500	FPT 517hp
<b>CR</b> Threshing: 450mm feed roller and two 560mm x 2.64m variable-speed rotors. Separation: threshing rotors and 1.56m x 400mm beater - 3.06sq m. Sieve area: 6.5sq m.					
CR 8.90 Revelation	£531,515	9.15m HCH	10.7m	12,500	FPT 544hp
CR 8.90 Revelation SmartTrax	£574,976	9.15m HCH	10.7m	12,500	FPT 544hp
CR 9.90 Revelation 12,500	£572,664	10.7m HCH	12.5m	12,500	FPT 600hp
CR 9.90 Revelation SmartTrax	£623,515	10.7m HCH	12.5m	12,500	FPT 600hp
CR 9.90 Revelation SmartTrax	£676,259	10.7m HCH	12.5m	14,500	FPT 600hp
CR10.90 Revelation SmartTrax Terraglide	£740,887	12.5m HCH	10.7m	14,500	FPT 639/700hp

*Note: CR10.90 highest power output available when chopping or unloading. CX7 - Ultra-Flow segmented rasp bar threshing drum standard, regular drum optional. Cutting tables: HCH - high capacity header; options - 760VG VariFeed 4.88m to 12.5m with 575mm hydraulic fore-aft knife position adjustment; MacDon FD2 7.6m to 15.2m articulated frame, rigid cutterbar draper. Slope compensation: TC - SmartSieve dynamic sieve action for up to 25% slopes and Opti-Fan variable-output ventilation working uphill and downhill; CX 5/6 - SmartSieve dynamic sieve action for up to 25% slopes, Opti-Fan variable-output ventilation and Opti-Speed variable-speed straw walkers for working uphill and downhill; Laterale - SmartSieve, Opti-Fan and OptiSpeed plus 18% slope side-to-side self-levelling chassis; CH 7 - SmartSieve dynamic sieve action for up to 25% slopes and Opti-Fan variable-output ventilation; CX 7/8 SL and CR - Opti-Clean self-levelling cleaning shoe for up to 17% slope compensation. Management: CR - IntelliSense automatic settings optimisation option. Guidance: CX, CH and CR - IntelliSteer satellite autosteering option. Traction: SmartTrax traction belts 61cm and 76cm; SmartTrax with Terraglide suspension 61cm, 72cm and 86cm. Four-wheel drive: CX, CH and CR £18,000. Distributor: New Holland Agriculture.*