

Your guide to buying a combine

Harvest may have only just drawn to a close, but that hasn't stopped most of the major manufacturers from revealing updates for their 2018 machines. All the latest specs and prices are listed in our complete five-page guide, compiled by **Peter Hill**

COMBINE HARVESTERS GUIDE – HARVEST 2018

Model	List price – £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make & max harvesting power / max unloading power (hp)
CASE-IH					
140 Series Threshing: one 76cm x 2.79m three-speed variator drive rotor. Separation: as for threshing – 2.80sq m. Sieve area: 5.52sq m					
5140 Cross Flow	£250,656	5.48	4.88-6.70	8,810	FPT 312hp
6140 Cross Flow	£287,350	6.70	5.48-6.10	10,570	FPT 400hp
7140 Cross Flow	£305,426	7.62	6.09-9.14	10,570	FPT 449hp
240 Series Threshing: one 76cm x 2.62m three-range hydro-drive rotor. Separation: as for threshing – 2.98sq m. Sieve area: 6.40sq m					
7240	£376,115	9.14	7.62-10.7	11,100	FPT 498hp
7240 Accutrac	£422,525	9.14	7.62-10.8	11,100	FPT 498hp
8240 X-Tra	£457,779	10.7	9.14-12.5	14,440	FPT 571hp
8240 Accutrac X-Tra	£498,164	10.7	9.14-12.6	14,440	FPT 571hp
9240 X-Tra	£494,660	12.5	9.14-10.7	14,440	FPT 634hp
9240 Accutrac X-Tra	£541,087	12.5	9.14-10.7	14,440	FPT 634hp
Note: X-Tra models equipped with Redekop MAV straw chopper and chaff distributor (optional on 7240) in addition to standard straw chopper. 'ST' (small tube) rotor standard on all models. Prices include 3050 Series table with 570mm fore-aft knife adjustment. Hydraulic side knives optional. Axial-Flow 140 Series combines have Cross Flow cleaning system for hillside compensation up to 12%; 240 Series have self-levelling shaker shoe assembly for 12% slope compensation. AFS AccuGuide GPS steering – 140 Series £13,878; 240 Series standard. Accutrac traction belt widths 61cm, 72cm and 86cm. 4wd option: 140 Series £16,781; 240 Series £16,781. Distributor: Case IH Agriculture.					
CLAAS					
Avero 200 Series Threshing: Separation drum + 1.06m x 45cm cylinder + beater. Separation: Four walkers + overhead agitator tine drum – 4.8sq m. Sieve area: 3.0sq m					
240	£139,621	4.9 C	3.7-5.4	5,600	Perkins 205hp
Tucano 300 Series Threshing: 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines – 6.78 sq m. Sieve area: 4.25sq m					
320	£176,350	6.2 V	3.7-5.4	6,500	M-B 245hp
Tucano 400 Series Threshing: Separation drum + 1.32m x 45cm cylinder + beater. Separation: Five walkers + overhead agitator tines – 7.26sq m. Sieve area: 4.7sq m					
420	£189,520	6.2 V	4.9-6.0	7,500	M-B 245hp
430	£200,160	6.2 V	4.9-6.0	8,000	M-B 286hp
Tucano 400 Series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: Six walkers + overhead agitator tines – 8.75sq m. Sieve area: 5.65sq m					
440	£219,240	6.8 V	6.0-7.7	8,500	M-B 286hp
450	£236,380	7.7 V	6.0-9.3	10,000	M-B 313hp
Tucano 500 Series Threshing: Separation drum + 1.58m x 45cm cylinder + beater. Separation: one 57cm x 4.2m vari-speed rotor – n/a sq m. Sieve area: 5.65sq m					
570	£247,300	7.7 V	6.0-9.3	10,000	M-B 354hp
Lexion 600 Series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Five walkers + overhead agitator tine drum – 8.23sq m. Sieve area: 4.80sq m					
620	£218,970	6.2 V	5.4-6.6	9,000	M-B 313hp
630	£227,280	6.8 V	6.0-7.7	9,000	M-B 354hp
630 Montana	£244,070	6.8 V	6.0-7.7	9,000	M-B 354hp
Lexion 600 Series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Six walkers + overhead agitator tine drum – 9.85sq m. Sieve area: 5.80sq m					
650	£257,600	7.7 V	6.0-9.3 V	10,000	M-B 354hp
660	£271,920	7.7 V	6.6-9.3 V	11,000	M-B 408hp
660 Terra Trac	£309,870	7.7 V	6.6-9.3 V	11,000	M-B 435hp
670	£291,050	9.3 V	6.6-9.3 V	11,000	M-B 435hp
670 Montana	£300,040	7.7 V	6.6-9.3 V	10,000	M-B 435hp
670 Terra Trac	£333,970	9.3 V	6.6-9.3 V	11,000	M-B 435hp
Lexion 700 Series Threshing: Separation drum + 1.42m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors – 4.32sq m. Sieve area: 5.10sq m					
740	£295,640	7.7 V	6.6-9.3 V	10,000	M-B 405hp
750	£361,530	9.3 V	6.6-9.3 V	10,000	M-B 435hp
750 Montana	£363,530	9.3 V	6.6-9.3 V	10,000	M-B 435hp
750 Terra Trac	£382,000	9.3 V	6.6-10.8 V	10,000	M-B 435hp
760	£389,110	9.3 V	7.5-10.8 V	11,000	Perkins 503hp
760 Terra Trac	£437,490	10.5 V	7.5-10.8 V	11,000	Perkins 503hp
760 Montana	£390,130	9.3 V	7.5-9.3 V	9,000	Perkins 503hp
Lexion 700 Series Threshing: Separation drum + 1.7m x 60cm cylinder + beater. Separation: Two 44.5cm x 4.2m vari-speed rotors – n/a sq m. Sieve area: 6.20sq m					
770	£436,520	10.5 V	9.3-10.8 V	12,800	M-B 585hp

COMBINE HARVESTERS GUIDE – HARVEST 2018

Model	List price – £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make & max harvesting power / max unloading power (hp)
770 Terra Trac	£487,110	12.3 V	9.3-12.3 V	12,800	M-B 585hp
780 Terra Trac	£527,480	12.3 V	10.5-12.3 V	13,500	M-B 625hp
Note: 40kph transmission optional on Lexion 750 Terra Trac and 760 Terra Trac. Montana - automatic chassis levelling 17% lateral, 6% fore-aft. 4-D dynamic sieve 20% slope compensation standard on Lexion 760, 770 and 780, optional on all other models. Laser Pilot laser-scanning auto steer system standard on Lexion 760, 770 and 780, optional on other models. GPS Pilot satellite-guided auto steer optional on all models. CEMOS settings advice system and CEMOS Automatic optional on all Lexion 600 and 700 Series combines. Terra Trac - rubber track suspension undercarriage with 635mm, 735mm or 890mm traction belts. Cutting tables: C - Contour, AC - Auto Contour, V - Auto Contour Vario (with fore-aft knife adjustment). Cruise Pilot automatic forward speed control optional on Lexion 780 - 650. 4wd optional on all models. Distributor: Claas UK.					
DEUTZ-FAHR					
6200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 5.28sq m. Sieve area: 4.22sq m					
6205 Farm-Line	£156,678	4.8	3.6-5.4	7,000	M-B 250hp
6205 Top-Line	£163,860	4.8	3.6-5.4	7,000	M-B 250hp
6200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers – 5.28sq m. Sieve area: 4.22sq m					
6205 HTS Farm-Line	£164,972	4.8	3.6-5.4	7,000	M-B 250hp
6205 HTS Top-Line	£172,154	4.8	3.6-5.4	7,000	M-B 250hp
7200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 7.36sq m. Sieve area: 5.28sq m					
C7205 Farm-Line	£207,294	5.4	4.2-7.2	8,500	M-B 309hp
C7205 Top-Line	£211,056	5.4	4.2-7.2	8,500	M-B 309hp
7200 Series Threshing: 1.27m x 60cm cylinder+ beater. Separation: 59cm diameter peg drum adjustable out of crop flow + five walkers – 7.36sq m. Sieve area: 5.28sq m					
C7205 TS Farm-Line	£218,409	6.3	4.8-7.2	8,500	M-B 309hp
C7205 TS Top-Line	£223,026	6.3	4.8-7.2	8,500	M-B 309hp
C7205 TSB Balance	£240,810	6.3	4.8-7.2	8,500	M-B 309hp
7200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation:Six walkers – 8.8sq m. Sieve area: 6.32sq m					
C7206 Farm-Line	£240,725	6.3	5.4-9.0	9,500	M-B 340hp
C7206 Top-Line	£246,453	6.3	5.4-9.0	9,500	M-B 340hp
C7206 Balance	£264,152	6.3	5.4-9.0	9,500	M-B 340hp
7200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers – 8.8sq m. Sieve area: 6.32sq m					
C7206 TS Farm-Line	£255,944	6.3	5.4-9.0	9,500	M-B 340hp
C7206 TS Top-Line	£261,672	6.3	5.4-9.0	9,500	M-B 340hp
C7206 TSB Balance	£279,371	6.3	5.4-9.0	9,500	M-B 340hp
9200 Series Threshing: 1.27m x 60cm cylinder + beater. Separation: Five walkers – 7.36sq m. Sieve area: 5.28sq m					
C9205 TS	£250,087	6.3	4.8-7.2	9,500	M-B 340hp
C9205 TSB Balance	£267,786	6.3	4.8-7.2	9,500	M-B 340hp
9200 Series Threshing: 1.52m x 60cm cylinder + beater. Separation: 59cm diameter peg drum adjustable out of crop flow + six walkers – 8.8sq m. Sieve area: 6.32sq m					
C9206 TS	£285,142	7.2	5.4-9.0	9,500	M-B 395hp
C9206 TSB Balance	£302,841	7.2	5.4-9.0	9,500	M-B 395hp
Note: HTS and TS – Turbo Separator with concave adjustable out of work for dry, brittle conditions. TSB Balance – automatic 20% lateral, 6% fore-aft self-levelling chassis; TSXB Balance available to special order with rear axle lift for 22% lateral, 28% uphill, 5% downhill self-levelling. Agrosky auto steering optional on C7200 and C9200 ranges. Distributor: SDF UK.					

FENDT

E Series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 6.72sq m. Sieve area: 4.67sq m					
5185E	£139,690	4.2 FF	4.8-6.0 FF	5,200	AGCO 176hp
5225E	£159,920	4.8 FF	6.0-7.6 FF or 5.5 PF	6,500	AGCO 218hp
L Series Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 7.62sq m. Sieve area: 4.67sq m					
5225L	£182,400	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
L Series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers – 7.62sq m. Sieve area: 4.67sq m					
5225L MCS	£190,090	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
5225L MCS ParaLevel	£224,690	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
L Series Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers – 8.30sq m. Sieve area: 5.58sq m					
6275L	£200,820	6.0FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
L Series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9sq m. Sieve area: 5.58sq m					
6275L MCS	£208,510	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
6275L MCS ParaLevel 4wd	£243,110	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
C Series Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers – 6.72sq m. Sieve area: 4.67sq m					
5275C	£218,380	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 276/306hp
5275C ParaLevel 2wd	£231,400	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
5275C ParaLevel 4wd	£245,380	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
C Series Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9sq m. Sieve area: 5.58sq m					
5275C ParaLevel Integrale 4wd	£264,430	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
6335C	£237,330	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
6335C ParaLevel 4wd	£262,900	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 320/360hp

COMBINE HARVESTERS GUIDE - HARVEST 2018

Model	List price – £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make & max harvesting power / max unloading power (hp)
6335C ParaLevel Integrale 4wd	£278,280	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 320/360hp
P Series Threshing: 1.68m x 60cm cylinder + beater + rethresher. Separation: 1.68m x 50cm peg drum + eight walkers – 10.47sq m. Sieve area: 5.30sq m					
8380P	£271,980	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
8380P Atrak	£323,540	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
8380P AutoLevel	£283,800	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
8410P	£288,050	7.7 PF	7.6 FF or 6.8-9.2 PF	12,500	AGCO 404hp
8410P Atrak	£339,610	7.7 PF	7.6 FF or 6.8-9.2 PF	12,500	AGCO 404hp
8410P AutoLevel	£299,130	7.7 PF	7.6 FF or 6.8-9.2 PF	10,500	AGCO 404hp
X Series Threshing: 1.7m x 60cm cylinder + beater + rotor-feeder (concave area - 1.9sq.m). Separation: Two 47.5cm x 4.2m variable speed hydro-drive rotors – 5.44sq m. Sieve area: 5.30sq m					
9490X	£350,680	10.74 PF	9.2 PF	12,500	AGCO 466/496hp
9490X Atrak	£402,240	10.74 PF	9.2 PF	12,500	AGCO 466/496hp
9490X AutoLevel	£355,100	9.2 PF	10.74 PF	10,500	AGCO 466/496hp
Note: Fendt P Series combines have eight narrow straw walkers for more intensive action within equivalent area of six conventional walkers. AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Boost power available when unloading. Cutting tables: FF – Free Flow; PF – Power Flow with extended cutterbar position and short conveyor belt behind. Chaff spreader and Constant flow ground speed adjusting feedrate standard on P Series and X Series; yield meter/moisture sensor standard on 8410P and 9490X. Auto-Guide xls GPS auto steering option £6210 on P Series and X Series. Atrak – 660mm traction belt on rubber block suspension undercarriage. 4wd: L Series £13,980; C Series £13,980; P Series £17,860; X Series £17,860. Distributor: Fendt UK & Ireland.					

JOHN DEERE

W300 Series Threshing: 1.1m x 50cm cylinder + 40cm dia pre-threshing drum. Separation: Five walkers + optional overhead agitator tine drum – 4.80sq m. Sieve area: 3.40sq m					
W330 PTC	£174,521	4.6	3.9-5.1	5,200	AGCO 206/213hp
W400 Series Threshing: 1.33m x 50cm cylinder. Separation: Six walkers + optional overhead agitator tine drum – 6.40sq m. Sieve area: 4.50sq m					
W440	£192,177	5.5	4.5-6.9	6,500	AGCO 235/249hp
W400 Series Threshing: 1.33m x 50cm cylinder + 40cm dia pre-threshing drum. Separation: Six walkers + optional overhead agitator tine drum – 6.40sq m. Sieve area: 4.50sq m					
W440 PTC	£203,406	5.5	4.5-6.9	7,600	AGCO 235/249hp
W500 Series Threshing: 1.4m x 66cm cylinder + 40cm dia beater. Separation: Five walkers + overhead agitator tine drum – 6.70sq m. Sieve area: 5.20sq m					
W540	£264,688	6.1	5.5-7.6	8,000 or 10,000	Deere 255/277hp
W540 HillMaster	£274,970	6.1	5.5-7.6	8,000	Deere 255/277hp
W550	£276,195	6.7	5.5-7.6	8,000 or 10,000	Deere 300/330hp
W550 HillMaster	£287,265	6.7	5.5-7.6	8,000	Deere 300/330hp
W600 Series Threshing: 1.67m x 66cm cylinder + 40cm dia beater. Separation: Six walkers + overhead agitator tine drum – 8sq m. Sieve area: 6.30sq m					
W650 ProDrive	£316,162	7.6	5.5-6.1	9,000 or 11,000	Deere 343/377hp
W650 HillMaster	£319,808	7.6	5.5-6.1	9,000	Deere 343/377hp
W660 ProDrive 40kph	£323,695	7.6	6.7	9,000 or 11,000	Deere 382/416hp
W660 HillMaster 40kph	£337,524	7.6	6.7	9,000 or 11,000	Deere 382/416hp
W660 ProDrive 40kph Tracks	£374,547	7.6	6.7	9,000 or 11,000	Deere 382/416hp
T500 Series Threshing: 1.4m x 66cm cylinder + 40cm dia beater. Separation: 14cm stripper roller + 50cm overshot beater + 80cm separator drum + 40cm beater (3.30sq m) + five walkers – 4.80sq m. Sieve area: 5.20sq m					
T550	£317,671	6.7	5.5-7.6	8,000 or 10,000	Deere 300/330hp
T550 HillMaster	£331,475	6.7	5.5-7.6	8,000	Deere 300/330hp
T560 ProDrive	£358,512	7.6	6.7	10,000	Deere 382/416hp
T560 ProDrive HillMaster	£373,684	7.6	6.7	10,000	Deere 382/416hp
T560 ProDrive Tracks	£409,364	7.6	6.7	10,000	Deere 382/416hp
T600 Series Threshing: 1.67m x 66cm cylinder + 40cm dia beater. Separation: 14cm stripper roller + 50cm overshot beater + 80cm separator drum + 40cm beater (4.0sq m) + six walkers – 5.80sq m. Sieve area: 6.30sq m					
T660 ProDrive	£375,485	9.15	7.6	9,000 or 11,000	Deere 382/416hp
T660 ProDrive HillMaster	£392,318	9.15	7.6	9,000 or 11,000	Deere 382/416hp
T660 ProDrive Tracks	£426,337	9.15	7.6	9,000 or 11,000	Deere 382/416hp
T670 ProDrive	£394,300	9.15	7.6-10.7	11,000	Deere 449/483hp
T670 ProDrive HillMaster	£410,651	9.15	7.6-10.7	11,000	Deere 449/483hp
T670 ProDrive Tracks	£445,152	9.15	7.6-10.7	11,000	Deere 449/483hp
S700 Series Threshing: feed drum + 76.2cm x 3.12m rotor. Separation: as for threshing – 3.0 or 3.09sq m. Sieve area: 5.20sq m					
S770 ProDrive	£405,897	9.15	7.6	10,600	Deere 392/449hp
S770 ProDrive Tracks	£454,555	9.15	7.6	10,600	Deere 392/449hp
S770 ProDrive HillMaster	£424,538	9.15	7.6	10,600	Deere 392/449hp
S780 ProDrive	£450,425	9.15	7.6-10.7	14,100	Deere 473/540hp
S780 ProDrive Tracks	£496,570	9.15	7.6-10.7	14,100	Deere 473/540hp
S780 ProDrive HillMaster	£460,124	9.15	n/a	10,600	Deere 473/540hp
S785 ProDrive	£480,362	10.7	9.15	14,100	Deere 500/570hp
S785 ProDrive Tracks	£522,581	10.7	9.15	14,100	Deere 500/570hp

COMBINE HARVESTERS GUIDE – HARVEST 2018

Model	List price – £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make & max harvesting power / max unloading power (hp)
S785 ProDrive HillMaster	£469,520	9.15	n/a	10,600	Deere 500/570hp
S790 ProDrive	£508,382	12.2	9.15-10.7	14,100	Deere 543/617hp
S790 ProDrive Tracks	£550,581	12.2	9.15-10.7	14,100	Deere 543/617hp
S790 ProDrive HillMaster	£485,374	9.15	n/a	10,600	Deere 543/617hp
Note: Selected models available with 'i' precision farming specifications, including JDLink, AutoTrac GPS auto steering and HarvestDoc crop recording. ProDrive – 40kph IVT hydrostatic transmission with auto two-speed gearbox and diff lock. HillMaster – automatic 15% chassis levelling plus 7% sieve compensation. Front end options – Premium Flow 6.7m, 7.6m, 9.15m, 10.7m and 12.2m tables with conveyor feed between forward-positioned knife and auger; 700D draper header with centre-feeding conveyors and anti-overspill auger. Tracks – 660mm traction belt on undercarriage with hydro-pneumatic suspension. Optional 4wd: £18,239 for all models with wheels or tracks. Distributor: John Deere.					

MASSEY FERGUSON

MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 6.72sq m. Sieve area: 4.67sq m					
7340	£139,690	4.2 FF	4.8-6.0 FF	5,200	AGCO 176hp
7344	£159,920	4.8 FF	6.0-7.6 FF or 5.5 PF	6,500	AGCO 218hp
MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: Five walkers – 7.62sq m. Sieve area: 4.67sq m					
7345 S	£182,400	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
MF 7300 Activa Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers – 7.62sq m. Sieve area: 4.67sq m					
7345 S MCS	£190,090	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
7345 S MCS ParaLevel 2wd	£210,710	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
7345 S MCS ParaLevel 4wd	£224,690	5.4	4.8-7.6 FF or 6.2 PF	8,600	AGCO 243hp
MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: Six walkers – 8.30sq m. Sieve area: 5.58sq m					
7347 S	£200,820	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 243hp
MF 7300 Activa Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9sq m. Sieve area: 5.58sq m					
7347 S MCS	£208,510	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276hp
7347 S MCS ParaLevel 2wd	£229,130	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
7347 S MCS ParaLevel 4wd	£243,110	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 276/306hp
MF 7300 Beta Threshing: 1.34m x 60cm cylinder + beater. Separation: 1.31m x 60cm peg drum with retractable concave + five walkers – 6.72sq m. Sieve area: 4.67sq m					
7360	£218,380	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 276/306hp
7360 ParaLevel 2wd	£231,400	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
7360 ParaLevel 4wd	£245,380	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
7360 ParaLevel Integrale 4wd	£264,430	6.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 276/306hp
MF 7300 Beta Threshing: 1.60m x 60cm cylinder + beater. Separation: 1.56m x 60cm peg drum with retractable concave + six walkers – 9sq m. Sieve area: 5.58sq m					
7370	£237,330	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	9,000	AGCO 320/360hp
7370 ParaLevel 2wd	£248,920	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 320/360hp
7370 ParaLevel 4wd	£262,900	7.0 FF	4.8-7.6 FF or 5.4-6.8 PF	8,600	AGCO 320/360hp
7370 ParaLevel Integrale 4wd	£278,280	6.0 FF	4.8-7.6 FF or 5.4-6.2 PF	8,600	AGCO 320/360hp
MF 7300 Centora Threshing: 1.68m x 60cm cylinder + beater + rethresher. Separation: 1.68m x 50cm peg drum + eight walkers – 10.47sq m. Sieve area: 5.30sq m					
7380	£271,980	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
7380 Atrak	£323,540	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
7380 AutoLevel	£283,800	7.7 PF	7.6 FF or 6.8-7.6 PF	10,500	AGCO 348/379hp
7382	£288,050	7.7 PF	7.6 FF or 6.8-9.2 PF	12,500	AGCO 404hp
7382 Atrak	£339,610	7.7 PF	7.6 FF or 6.8-9.2 PF	12,500	AGCO 404hp
7382 AutoLevel	£299,130	7.7 PF	7.6 FF or 6.8-9.2 PF	10,500	AGCO 404hp
MF 9300 Delta Threshing: 1.7m x 60cm cylinder + beater + rotor-feeder (concave area - 1.9sq.m). Separation: Two 47.5cm x 4.2m variable speed hydro-drive rotors – 5.44sq m. Sieve area: 5.30sq m					
9380	£350,680	10.74 PF	9.2 PF	12,500	AGCO 466/496hp
9380 Atrak	£402,240	10.74 PF	9.2 PF	12,500	AGCO 466/496hp
9380 AutoLevel	£355,100	9.2 PF	10.74 PF	10,500	AGCO 466/496hp

Note: MF Centora models have eight narrow straw walkers for more intensive action within equivalent area of six conventional walkers. AutoLevel 12% slope, ParaLevel 4wd 20% slope, 2wd 15% automatic side-to-side chassis levelling; ParaLevel Integrale adds 30% uphill compensation. Boost power available when unloading. Cutting tables: FF – Free Flow; PF – Power Flow with extended cutterbar position and short conveyor belt behind. Chaff spreader and Constant Flow ground speed adjusting feedrate standard on 7300 Centora and 9300 Delta models; yield meter/moisture sensor standard on MF7382 and MF9380 Delta. Auto-Guide xls GPS auto steering option £6210 on Centora and Delta models. Atrak – 660mm traction belt on rubber block suspension undercarriage. 4wd: Activa £13,980; Beta £13,980; Centora £17,860; Delta £17,860. Distributor: Massey Ferguson UK & Ireland.

NEW HOLLAND

TC 4 Threshing: 1.04m x 60cm cylinder + beater. Separation: 60cm peg drum + four walkers – 4sq m. Sieve area: 3.27sq m					
TC4.90	£139,793	3.9	4.5	5,000	NH 175hp
TC 5 Threshing: 1.3m x 60cm cylinder + beater. Separation: 60cm peg drum + five walkers - 5sq m. Sieve area: 4.13sq m					
TC5.70 SmartSieve	£177,390	5.49	4.88	5,200	NH 175hp
TC5.80 SmartSieve	£191,600	5.49	4.88	6,400	NH 227hp
TC5.90 SmartSieve	£199,603	5.49	4.88	6,400	NH 258hp

COMBINE HARVESTERS GUIDE - HARVEST 2018

Model	List price – £ (with recommended table)	Recommended table (m)	Other table sizes available (m)	Grain tank (litres)	Engine make & max harvesting power / max unloading power (hp)
CX 5 Threshing: 1.3m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + five walkers – 7.37sq m. Sieve area: 4.32sq m					
CX 5.80	£218,706	6.10	5.18-6.70	8,300	NH 258hp
CX 5.90	£229,629	6.70	6.10	8,300	NH 300hp
CX 5.90 Laterale	£252,246	6.70	6.10	8,300	NH 300hp
CX 6 Threshing: 1.56m x 60cm cylinder + 39cm beater. Separation: 59cm peg drum + straw flow beater + six walkers – 8.84sq m. Sieve area: 5.21sq m					
CX 6.80	£246,122	6.10	7.32	9,300	NH 303hp
CX 6.90	£259,034	7.62	6.10	9,300	FPT 340hp
CX 6.90 Laterale	£279,685	7.62	6.10	9,300	FPT 340hp
CX 7 Threshing: 1.3m x 75cm cylinder + 61cm beater. Separation: 75cm peg drum (2.11sq m) + five walkers – 5.56sq m. Sieve area: 5.40sq m					
CX 7.80 SL	£268,977	6.10	5.49-7.62	9,000	FPT 340hp
CX 7.90 SL	£280,943	6.70	5.49-7.62	10,000	FPT 374hp
CX 7.90 SL SmartTrax	£315,255	6.70	5.49-7.62	10,000	FPT 374hp
CX 8 Threshing: 1.56m x 75cm cylinder + 61cm beater. Separation: 75cm diameter peg drum (2.54sq m) + six walkers – 6.68sq m. Sieve area: 6.50sq m					
CX 8.70 SL	£295,415	7.6	6.1	11,500	FPT 374hp
CX 8.80 SL	£316,465	7.6	9.15	11,500	FPT 401hp
CX 8.80 SL SmartTrax	£349,439	7.6	9.15	11,500	FPT 401hp
CX 8.85 SL	£326,303	9.15	7.32	12,500	FPT 450hp
CX 8.85 SL SmartTrax	£358,792	9.15	7.32	12,500	FPT 450hp
CX 8.90 SL	£332,683	9.15	7.32	12,500	FPT 490hp
CX 8.90 SL SmartTrax	£365,085	9.15	7.32	12,500	FPT 490hp
CR Threshing: 450mm feed roller + two 43cm x 2.64m variable-speed rotors. Separation: threshing rotors + 1.3m x 40cm beater – 2.43sq m. Sieve area: 5.40sq m					
CR 7.90 Revelation	£335,387	7.62	9.15	11,500	FPT 449hp
CR 8.80 Revelation	£355,294	9.15	7.62	12,500	FPT 517hp
CR 8.80 Revelation SmartTrax	£399,214	9.15	7.62	12,500	FPT 517hp
CR Threshing: 450mm feed roller + two 56cm x 2.64m variable speed rotors. Separation: threshing rotors + 1.56m x 40cm beater – 3.06sq m. Sieve area: 6.50sq m					
CR 8.90 Revelation	£379,205	9.15	10.7	12,500	FPT 517hp
CR 8.90 Revelation SmartTrax	£414,783	9.15	10.7	12,500	FPT 517hp
CR 9.80 Revelation	£413,116	10.7	12.5	12,500	FPT 571hp
CR 9.80 Revelation SmartTrax	£452,687	10.7	12.5	12,500	FPT 571hp
CR 9.90 Revelation SmartTrax	£479,926	10.7	12.5	14,500	FPT 571hp
CR10.90 Revelation SmartTrax	£554,239	12.5	10.7	14,500	FPT 700hp
Note: SmartSieve – dynamic 25% slope compensation; Laterale – 18% lateral self-levelling chassis plus SmartSieve dynamic slope compensation; SL – automatic 17% self-levelling cleaning shoe; CX 7/8 and CR models have OptiClean self-levelling cleaning shoe. VariFeed table with 575mm extending knife optional on all models. OptiSpeed variable speed straw walkers standard on CX combines. SmartSteer scanning laser auto steering optional for £3843 on all CX and CR models. IntelliSteer GPS auto steering optional for £9062 on CX7/8 and CR models. SmartTrax traction belts 61cm and 76cm; SmartTrax with Terraglide suspension 61cm, 72cm and 86cm. Optional 4wd: CX and CR £14,185. Distributor: New Holland Agriculture.					

ROSTSELMASH / VERSATILE

RSM Series Threshing: 1.65m x 800mm cylinder + beater - 3.3sq m. Separation: 1.65m x 800mm peg drum + six walkers – 9.4sq m. Sieve area: 7.1sq m					
RSM 161 Tetra	poa	6.0m	7.0-9.0m	10,500	Cummins 380hp
RT 400 Series Threshing: Two feeder house separation drums + beater + 76cm diameter rotor. Separation: as for threshing – 5.4sq m. Sieve area: 5.20sq m					
RT 490	poa	7m	6-9m	11,980	Cummins 490hp
Note: Optional 4wd £poa Distributor: JPM Agricultural.					

IMPRESSIVELY STURDY.
RAISING YOUR STANDARDS.





Kramer telehandler up to 9 m stacking height.
www.kramer.de/telehandler

